

CROSSTRAIL HYDRAULIC DISC



Nero / Blu Cangiante / Nero Riflettente

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized A1 Premium Aluminum, Fitness Geometry, butted tubing, Plug + Play rack/fender mounts
FORCELLA	SR Suntour NEX w/ Specialized Fitness Brain technology, 1-1/8" steerer, QR, fender mounts, 43mm offset, 55mm of travel
ATTACCO	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
MANUBRIO	Double-butted alloy, 9-degree backsweep, 31.8mm
MANOPOLE	Specialized Body Geometry XCT, lock-on
FRENO ANT.	Promax Solve, hydraulic disc, post-mount, 160mm
FRENO POST.	Promax Solve, hydraulic disc, post-mount, 160mm
DERAGL. ANT.	Shimano Tourney, 3-speed, top-swing
CAMBIO POST.	Shimano Altus, 7-/8-speed
COMANDI	Shimano Acera, 8-speed
CASSETTA	SunRace, 8-speed, 11-34t
CATENA	KMC X8EPT, 8-speed, anti-corrosion coating w/ reusable Missing Link™
GUARNITURA	Shimano Tourney, 3-piece, square-taper
INGRANAGGI	48/38/28T
MOVIM. CENTR.	BSA, 68mm, square taper
CERCHI	700C disc, 6061 aluminum, double-wall
MOZZO ANT.	Alloy, 6-bolt disc, loose ball bearing, quick-release, 32h
MOZZO POST.	Alloy, 6-bolt disc, 8-/9-speed freehub, loose ball bearing, quick-release, 32h
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Trigger Sport Reflect, 60 TPI, wire bead, 700x38mm
PNEUMATICO POST.	Trigger Sport Reflect, 60 TPI, wire bead, 700x38mm
SELLA	Specialized Canopy Sport, steel rails, 155mm
REGGISSELLA	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

CROSSTRAIL HYDRAULIC DISC	S	M	L	XL
Stack (mm)	586	602	621	640
Reach (mm)	390	400	412	426
Lunghezza Tubo sterzo (mm)	100	115	135	155
Angolo sterzo (degrees)	70	70.5	70.5	70.5
Altezza Mov. Centr. (mm)	288	288	288	288
BB Drop (mm)	65	65	65	65
Trail (mm)	84	81	81	81
Lunghezza intera forcella (mm)	465	465	465	465
Offset forcella / Rake (mm)	42	42	42	42
Avancorsa (mm)	628	638	657	678
Lunghezza Batticatena (mm)	445	445	445	445
Interasse (mm)	1065	1075	1094	1115
Lunghezza Tubo Orizz. virtuale (mm)	569	584	602	622
Altezza standover (mm)	722	742	802	843
Lunghezza piantone (mm)	400	450	500	550
Angolo Sella (degrees)	73	73	73	73
Lunghezza Pedivella (mm)	170	175	175	175
Larghezza Manubrio (mm)	660	660	660	660
Lunghezza attacco manubrio (mm)	60	70	80	90
Larghezza sella (mm)	155	155	155	155
Lunghezza reggisella (mm)	350	350	350	350

ART. NR.	DESCRIZIONE	COLORE	MISURA
92418-7002	CROSSTRAIL HYDRO DISC INTL	BLK/CMLN/NRBLK	S
92418-7003			M
92418-7004			L
92418-7005			XL