

CROSSTRAIL SPORT DISC



Avio Lucido / Rosso Rocket / Nero Riflettente

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

TELAIO	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack & fender mounts
FORCELLA	SR Suntour NEX w/ Specialized Fitness Brain technology, 1-1/8" steerer, QR, fender mounts, 43mm offset, 55mm of travel
ATTACCO	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
MANUBRIO	Double-buttet alloy, 9-degree backsweep, 31.8mm
MANOPOLE	Specialized Body Geometry XCT, lock-on
FRENO ANT.	Tektro HD-R305, hydraulic disc, resin pads, post-mount, 160mm Center Lock™
FRENO POST.	Tektro HD-R310, hydraulic disc, resin pads, flat-mount, 160mm
DERAGL. ANT.	microSHIFT Marvo LT, 31.8mm clamp
CAMBIO POST.	Shimano Alivio, Shadow Design, SGS cage, 9-speed
COMANDI	microSHIFT, 9-speed
CASSETTA	SunRace, 9-Speed, 11-36t
CATENA	KMC X9EPT, 9-speed, anti-corrosion coating w/ reusable Missing Link™
GUARNITURA	FSA Alpha Drive, 3-piece
INGRANAGGI	48/32T
MOVIM. CENTR.	BSA, 68mm, square taper
CERCHI	700C disc, 6061 aluminum, double-wall
MOZZO ANT.	Shimano Center Lock™ disc, loose ball bearings, quick-release, 32h
MOZZO POST.	Shimano Center Lock™ disc, loose ball bearings, quick-release, 10-speed freehub, 32h
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Trigger Sport Reflect, 60 TPI, wire bead, 700x38mm
PNEUMATICO POST.	Trigger Sport Reflect, 60 TPI, wire bead, 700x38mm
SELLA	Specialized Canopy Sport, steel rails, 155mm
REGGISSELLA	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

CROSSTRAIL SPORT DISC	S	M	L	XL
Lunghezza piantone c/f (mm)	400	450	500	550
Lunghezza Tubo Orizz. virtuale (mm)	572	587	604	624
BB Drop (mm)	65	65	65	65
Lunghezza Batticatena (mm)	445	445	445	445
Angolo Sella (degrees)	73	73	73	73
Angolo sterzo (degrees)	70	70.5	70.5	70.5
Offset forcella / Rake (mm)	42	42	42	42
Trail (mm)	87	84	84	84
Avancorsa (mm)	630	641	655	680
Interasse (mm)	1067	1078	1096	1117
Altezza standover (mm)	740	776	813.3	850
Lunghezza Tubo sterzo (mm)	110	125	145	165
Reach (mm)	390	400	412	426
Stack (mm)	594	611	630	648
Lunghezza Pedivella (mm)	170	175	175	175
Larghezza Manubrio (mm)	660	660	660	660
Lunghezza attacco manubrio (mm)	60	70	80	90
Larghezza sella (mm)	155	155	155	155
Lunghezza reggisella (mm)	350	350	350	350

ART. NR.	DESCRIZIONE	COLORE	MISURA
92419-6002	CROSSTRAIL SPORT INT	STRMGY/RKTRED/BLK	S
92419-6003			M
92419-6004			L
92419-6005			XL