



Azzurro / Rosso Razzo / Nero

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized A1 Premium Aluminum, single-butted, ZeroStack head tube, 135mm rear hub spacing, forged dropouts, replaceable derailleur hanger
FORCELLA	SR Suntour XCT, Multi-Circuit Damping, air spring, hydraulic lockout, QR, 40mm offset, 70mm of travel
ATTACCO	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
MANUBRIO	Double-butted alloy, 9-degree backsweep, 31.8mm
MANOPOLE	Specialized Body Geometry XCT, lock-on
FRENO ANT.	Tektro Auriga, hydraulic disc, resin pads, 160mm
FRENO POST.	Tektro Auriga, hydraulic disc, resin pads, 160mm
CAMBIO POST.	Shimano Alivio, Shadow Design, SGS cage, 9-speed
COMANDI	Shimano Alivio, 9-speed
CASSETTA	SunRace, 9-Speed, 11-36t
CATENA	KMC X9EPT, 9-speed, anti-corrosion coating w/ reusable Missing Link™
GUARNITURA	Forged alloy, 152mm
INGRANAGGI	Steel, 30T
MOVIM. CENTR.	BSA, square taper, cartridge bearings
CERCHI	24", double-wall aluminum
MOZZO ANT.	Alloy, 6-bolt disc, 110mm spacing, loose ball bearings, QR, 32h
MOZZO POST.	Alloy, 6-bolt disc, 135mm spacing, 9-speed freehub, loose ball bearings, QR, 32h
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Big Roller, 60 TPI, wire bead, 24x2.8"
PNEUMATICO POST.	Big Roller, 60 TPI, wire bead, 24x2.8"
SELLA	Specialized Kids' Henge

RIPROCK COMP 24	11
Lunghezza piantone c/f (mm)	567
Lunghezza Tubo Orizz. virtuale (mm)	510
BB Drop (mm)	61
Altezza Mov. Centr. (mm)	264
Lunghezza Batticateni (mm)	420
Angolo Sella (degrees)	73
Angolo sterzo (degrees)	69
Offset forcella / Rake (mm)	40
Interasse (mm)	989
Altezza standover (mm)	608
Lunghezza Tubo sterzo (mm)	115
Reach (mm)	336.5
Lunghezza Pedivella (mm)	152
Larghezza Manubrio (mm)	600
Lunghezza attacco manubrio (mm)	60
Larghezza sella (mm)	135
Lunghezza reggisella (mm)	300

ART. NR.	DESCRIZIONE	COLORE	MISURA
96519-5211	RIPROCK COMP 24 INT	NICEBLU/RKTRED/BLK	11