



Grigio / Verde Fluo

<b>SPECIFICHE TECNICHE</b>	<b>Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.</b>
TELAIO	Specialized A1 Premium Aluminum, single-butted, ZeroStack head tube, 135mm rear hub spacing, forged dropouts, replaceable derailleur hanger
FORCELLA	SR Suntour XCT, coil spring, preload adjust, 60mm of travel
ATTACCO	3D-forged alloy, 4-bolt, 6-degree rise, 25.4mm clamp, 60mm
MANUBRIO	580mm, 5-degree backsweep, 25.4mm
MANOPOLE	Specialized, slip-on
FRENO ANT.	Mechanical disc, organic pads, 6-bolt, tool-less reach adjust, 160mm
FRENO POST.	Mechanical disc, organic pads, 6-bolt, tool-less reach adjust, 160mm
CAMBIO POST.	Shimano Tourney TX, 7-speed
COMANDI	Shimano Tourney, Revo 7-speed
CASSETTA	SunRace, 7-Speed, 11-34t
CATENA	KMC Z51 EPT, anti-rust coating, 7-speed
GUARNITURA	Forged alloy, 127mm
INGRANAGGI	Steel, 30T
MOVIM. CENTR.	BSA, square taper
CERCHI	20", double-wall aluminum
MOZZO ANT.	Alloy, 6-bolt disc, 110mm spacing, loose ball bearings, QR, 32h
MOZZO POST.	Alloy, 6-bolt disc, 135mm spacing, 7-speed freehub, loose ball bearings, QR, 28h
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Big Roller, 60 TPI, wire bead, 20x2.8"
PNEUMATICO POST.	Big Roller, 60 TPI, wire bead, 20x2.8"
SELLA	Specialized Kids' Henge

<b>RIPROCK 20</b>	<b>9</b>
Lunghezza piantone c/f (mm)	279
Lunghezza Tubo Orizz. virtuale (mm)	465
BB Drop (mm)	37.5
Altezza Mov. Centr. (mm)	237
Lunghezza Batticateni (mm)	390
Angolo Sella (degrees)	73
Angolo sterzo (degrees)	69
Offset forcella / Rake (mm)	40
Interasse (mm)	909.5
Altezza standover (mm)	528
Lunghezza Tubo sterzo (mm)	115
Reach (mm)	306
Lunghezza Pedivella (mm)	127
Larghezza Manubrio (mm)	580
Lunghezza attacco manubrio (mm)	60
Larghezza sella (mm)	135
Lunghezza reggisella (mm)	300

<b>ART. NR.</b>	<b>DESCRIZIONE</b>	<b>COLORE</b>	<b>MISURA</b>
B6516-8009	RIPROCK 20 INT	CARBGRY/HYP/CLGRY	9