



Carbonio / Argento Olografico

S-WORKS EPIC EVO	S	M	L	XL
Stack (mm)	595	605	619	638
Reach (mm)	398	423	446	465
Lunghezza Tubo sterzo (mm)	95	105	120	140
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5
Altezza Mov. Centr. (mm)	340	340	340	340
BB Drop (mm)	32	32	32	32
Trail (mm)	99	99	99	99
Lunghezza intera forcella (mm)	526	526	526	526
Offset forcella / Rake (mm)	43	43	43	43
Avancorsa (mm)	667	695	723	749
Lunghezza Batticatena (mm)	438	438	438	438
Interasse (mm)	1103	1132	1159	1186
Lunghezza Tubo Orizz. virtuale (mm)	571	599	626	650
Altezza standover (mm)	772	777	782	804
Lunghezza piantone (mm)	400	434	470	520
Angolo Sella (degrees)	73.8	73.8	73.8	73.8
Lunghezza Pedivella (mm)	170	175	175	175
Larghezza Manubrio (mm)	760	760	760	760
Lunghezza attacco manubrio (mm)	60	75	75	75
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	361	411	411	411

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

TELAIO	S-Works FACT 12m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel
AMMORTIZZATORE	Custom RockShox Micro Brain shock w/ Spike Valve, AUTOSAG, 51x257mm
FORCELLA	FOX Factory Step-Cast 34, Fit4 damper, Kashima, Boost™, 44mm offset, 120mm of travel
ATTACCO	S-Works SL, alloy, titanium bolts, 6-degree rise
MANUBRIO	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
MANOPOLE	Specialized Trail Grips
FRENO ANT.	Shimano XTR Race M-9100
FRENO POST.	Shimano XTR Race M-9100
CAMBIO POST.	Shimano XTR M9100, 12-speed, Shadow Plus
COMANDI	Shimano XTR M9100, 12-speed
CASSETTA	Shimano XTR M9100, 12-speed, 10-51t
CATENA	Shimano XTR M9100, 12-speed
GUARNITURA	Race Face Next SL, 170/175mm
INGRANAGGI	Alloy, 32T
MOVIM. CENTR.	Threaded, 30mm spindle
CERCHI	Roval Control SL, hookless carbon, 25mm internal width, tubeless-ready, hand-built
MOZZO ANT.	Roval Control SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
MOZZO POST.	Roval Control SL, DT Swiss Star Ratchet, 54t engagement, DT Swiss Microspline driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Competition Race
PNEUMATICO ANT.	Ground Control, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, GRID casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base, 143mm
REGGISELLA	FOX Factory Transfer, Kashima, Shimano Ispc-EV lever (S: 100mm, M-XL: 125mm)

ART. NR.	DESCRIZIONE	COLORE	MISURA
90319-0002	EPIC SW CARBON EVO 29	Carbonio / Argento Olografico	S
90319-0003			M
90319-0004			L
90319-0005			XL