



Grigio Tortora Lucido / Rosso Rocket / Cremisi

| S-WORKS EPIC SRAM AXS | S | M | L | XL |
|-------------------------------------|-------|-------|-------|-------|
| Stack (mm) | 588 | 597 | 611 | 630 |
| Reach (mm) | 408 | 433 | 456 | 475 |
| Lunghezza Tubo sterzo (mm) | 95 | 105 | 120 | 140 |
| Angolo sterzo (degrees) | 69,5 | 69,5 | 69,5 | 69,5 |
| Altezza Mov. Centr. (mm) | 332 | 332 | 332 | 332 |
| BB Drop (mm) | 38,9 | 38,9 | 38,9 | 38,9 |
| Trail (mm) | 94 | 94 | 94 | 94 |
| Lunghezza intera forcella (mm) | 506 | 506 | 506 | 506 |
| Offset forcella / Rake (mm) | 42 | 42 | 42 | 42 |
| Avancorsa (mm) | 659 | 687 | 715 | 742 |
| Lunghezza Batticatena (mm) | 438 | 438 | 438 | 438 |
| Interasse (mm) | 1094 | 1123 | 1151 | 1177 |
| Lunghezza Tubo Orizz. virtuale (mm) | 568 | 596 | 623 | 647 |
| Altezza standover (mm) | 764 | 770 | 776 | 799 |
| Lunghezza piantone (mm) | 400 | 434 | 470 | 520 |
| Angolo Sella (degrees) | 74,75 | 74,75 | 74,75 | 74,75 |
| Lunghezza Pedivella (mm) | 170 | 175 | 175 | 175 |
| Larghezza Manubrio (mm) | 760 | 760 | 760 | 760 |
| Lunghezza attacco manubrio (mm) | 60 | 75 | 75 | 90 |
| Larghezza sella (mm) | 155 | 143 | 143 | 143 |
| Lunghezza reggisella (mm) | 350 | 400 | 400 | 400 |

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

| | |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| TELAIO | S-Works FACT 12m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel |
| AMMORTIZZATORE | Custom RockShox Micro Brain shock w/ Spike Valve, AUTOSAG, 51x257mm |
| FORCELLA | RockShox SID Brain Ultimate, top-adjust Brain Fade, tapered carbon crown and steerer, 15x110mm Maxle® Stealth thru-axle, 42mm offset, 100mm of travel |
| ATTACCO | S-Works SL, alloy, titanium bolts, 6-degree rise |
| MANUBRIO | S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm |
| MANOPOLE | Specialized Trail Grips |
| FRENO ANT. | SRAM Level Ultimate, hydraulic disc |
| FRENO POST. | SRAM Level Ultimate, hydraulic disc |
| CAMBIO POST. | SRAM XX1 Eagle AXS |
| COMANDI | SRAM XX1 Eagle AXS, trigger, 12-speed |
| CASSETTA | SRAM XG-1299 Eagle, 10-50t |
| CATENA | SRAM XX1 (Rainbow) |
| GUARNITURA | QUARQ XX1 Eagle Power Meter, Boost™ 148, DUB, 170/175mm |
| INGRANAGGI | Alloy, 32T |
| MOVIM. CENTR. | SRAM DUB, threaded BB |
| CERCHI | Roval Control SL, hookless carbon, 25mm internal width, tubeless-ready, hand-built |
| MOZZO ANT. | Roval Control SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h |
| MOZZO POST. | Roval Control SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h |
| RAGGI | DT Swiss Competition Race |
| PNEUMATICO ANT. | Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3" |
| PNEUMATICO POST. | Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3" |
| SELLA | Body Geometry S-Works Power, carbon fiber rails, carbon fiber base, 143mm |
| REGGISELLA | S-Works FACT carbon, 10mm setback, 30.9mm |

| ART. NR. | DESCRIZIONE | COLORE | MISURA |
|------------|----------------------------|-----------------------------------------|--------|
| 90320-0002 | EPIC SW CARBON SRAM AXS 29 | Grigio Tortora / Rosso Rocket / Cremisi | S |
| 90320-0003 | | | M |
| 90320-0004 | | | L |
| 90320-0005 | | | XL |