



Camaleonte / Scritta Olografia

S-WORKS EPIC SHIMANO XTR	S	M	L	XL
Stack (mm)	588	597	611	630
Reach (mm)	408	433	456	475
Lunghezza Tubo sterzo (mm)	95	105	120	140
Angolo sterzo (degrees)	69.5	69.5	69.5	69.5
Altezza Mov. Centr. (mm)	332	332	332	332
BB Drop (mm)	38.9	38.9	38.9	38.9
Trail (mm)	94	94	94	94
Lunghezza intera forcella (mm)	506	506	506	506
Offset forcella / Rake (mm)	42	42	42	42
Avancorsa (mm)	659	687	715	742
Lunghezza Batticatena (mm)	438	438	438	438
Interasse (mm)	1094	1123	1151	1177
Lunghezza Tubo Orizz. virtuale (mm)	568	596	623	647
Altezza standover (mm)	764	770	776	799
Lunghezza piantone (mm)	400	434	470	520
Angolo Sella (degrees)	74.75	74.75	74.75	74.75
Lunghezza Pedivella (mm)	170	175	175	175
Larghezza Manubrio (mm)	760	760	760	760
Lunghezza attacco manubrio (mm)	60	75	75	90
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	350	400	400	400

SPECIFICHE TECNICHE **Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

TELAIO	S-Works FACT 12m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel
AMMORTIZZATORE	Custom RockShox Micro Brain shock w/ Spike Valve, AUTOSAG, 51x257mm
FORCELLA	RockShox SID Brain Ultimate, top-adjust Brain Fade, tapered carbon crown and steerer, 15x110mm Maxle® Stealth thru-axle, 42mm offset, 100mm of travel
ATTACCO	S-Works SL, alloy, titanium bolts, 6-degree rise
MANUBRIO	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
MANOPOLE	Specialized Trail Grips
FRENO ANT.	Shimano XTR Race M-9100
FRENO POST.	Shimano XTR Race M-9100
CAMBIO POST.	Shimano XTR M9100, 12-speed, Shadow Plus
COMANDI	Shimano XTR M9100, 12-speed
CASSETTA	Shimano XTR M9100, 12-speed, 10-51t
CATENA	Shimano XTR M9100, 12-speed
GUARNITURA	Race Face Next SL, 170/175mm
INGRANAGGI	Alloy, 32T
MOVIM. CENTR.	Threaded, 30mm spindle
CERCHI	Roval Control SL, hookless carbon, 25mm internal width, tubeless-ready, hand-built
MOZZO ANT.	Roval Control SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
MOZZO POST.	Roval Control SL, DT Swiss Star Ratchet, 54t engagement, DT Swiss Microspline driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Competition Race
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base, 143mm
REGGISELLA	S-Works FACT carbon, 10mm setback, 30.9mm

ART. NR.	DESCRIZIONE	COLORE	MISURA
90320-0302	EPIC SW CARBON SHIMANO 29	Camaleonte / Scritta Olografia	S
90320-0303			M
90320-0304			L
90320-0305			XL