



Nero / Petrolio Cangiante

EPIC PRO CARBON	S	M	L	XL
Stack (mm)	588	597	611	630
Reach (mm)	408	433	456	475
Lunghezza Tubo sterzo (mm)	95	105	120	140
Angolo sterzo (degrees)	69.5	69.5	69.5	69.5
Altezza Mov. Centr. (mm)	332	332	332	332
BB Drop (mm)	38.9	38.9	38.9	38.9
Trail (mm)	94	94	94	94
Lunghezza intera forcella (mm)	506	506	506	506
Offset forcella / Rake (mm)	42	42	42	42
Avancorsa (mm)	659	687	715	742
Lunghezza Batticatena (mm)	438	438	438	438
Interasse (mm)	1094	1123	1151	1177
Lunghezza Tubo Orizz. virtuale (mm)	568	596	623	647
Altezza standover (mm)	764	770	776	799
Lunghezza piantone (mm)	400	434	470	520
Angolo Sella (degrees)	74.75	74.75	74.75	74.75
Lunghezza Pedivella (mm)	170	175	175	175
Larghezza Manubrio (mm)	760	760	760	760
Lunghezza attacco manubrio (mm)	60	70	80	90
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	350	400	400	400

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.	
TELAIO	Specialized FACT 11m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel
AMMORTIZZATORE	Custom RockShox Micro Brain shock w/ Spike Valve, AUTOSAG, 51x257mm
FORCELLA	RockShox SID Brain 29, Solo Air, top-adjust Brain Fade, 15x110mm Maxle® Stealth thru-axle, 42mm offset, 100mm of travel
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Level TLM, hydraulic disc
FRENO POST.	SRAM Level TLM, hydraulic disc
CAMBIO POST.	SRAM X01 Eagle, 12-speed
COMANDI	SRAM X01 Eagle, trigger, 12-speed
CASSETTA	SRAM XG-1295 Eagle, 12-speed, 10-50t
CATENA	SRAM GX Eagle, 12-speed
GUARNITURA	SRAM X1 carbon Eagle, Boost™ 148, DUB, 170/175mm, 32T
INGRANAGGI	Alloy, 32T
MOVIM. CENTR.	SRAM DUB, threaded BB
CERCHI	Roval Control Carbon, 25mm internal width, tubeless-ready
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
MOZZO POST.	DT Swiss 350, Star Ratchet, 36t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power, Hollow Titanium rails, 143mm
REGGISELLA	Carbon, single-bolt, 30.9mm

ART. NR.	DESCRIZIONE	COLORE	MISURA
90320-1102	EPIC PRO CARBON 29	Nero / Petrolio Cangiante	S
90320-1103			M
90320-1104			L
90320-1105			XL