

EPIC EXPERT EVO CARBON 29



Nero Satinato / Grigio Tortora

| EPIC EXPERT CARBON EVO | S | M | L | XL |
|-------------------------------------|------|------|------|------|
| Stack (mm) | 595 | 605 | 619 | 638 |
| Reach (mm) | 398 | 423 | 446 | 465 |
| Lunghezza Tubo sterzo (mm) | 95 | 105 | 120 | 140 |
| Angolo sterzo (degrees) | 68.5 | 68.5 | 68.5 | 68.5 |
| Altezza Mov. Centr. (mm) | 340 | 340 | 340 | 340 |
| BB Drop (mm) | 32 | 32 | 32 | 32 |
| Trail (mm) | 99 | 99 | 99 | 99 |
| Lunghezza intera forcella (mm) | 526 | 526 | 526 | 526 |
| Offset forcella / Rake (mm) | 43 | 43 | 43 | 43 |
| Avancorsa (mm) | 667 | 695 | 723 | 749 |
| Lunghezza Batticateni (mm) | 438 | 438 | 438 | 438 |
| Interasse (mm) | 1103 | 1132 | 1159 | 1186 |
| Lunghezza Tubo Orizz. virtuale (mm) | 571 | 599 | 626 | 650 |
| Altezza standover (mm) | 772 | 777 | 782 | 804 |
| Lunghezza piantone (mm) | 400 | 434 | 470 | 520 |
| Angolo Sella (degrees) | 73.8 | 73.8 | 73.8 | 73.8 |
| Lunghezza Pedivella (mm) | 170 | 175 | 175 | 175 |
| Larghezza Manubrio (mm) | 750 | 750 | 750 | 750 |
| Lunghezza attacco manubrio (mm) | 60 | 70 | 70 | 80 |
| Larghezza sella (mm) | 155 | 143 | 143 | 143 |
| Lunghezza reggisella (mm) | 361 | 411 | 411 | 411 |

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

| | |
|------------------|---|
| TELAIO | Specialized FACT 11m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel |
| AMMORTIZZATORE | Custom RockShox Micro Brain shock w/ Spike Valve, AUTOSAG, 51x257mm |
| FORCELLA | FOX Performance Step-Cast 34, Grip damper, Boost™, 44mm offset, 120mm of travel |
| ATTACCO | Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise |
| MANUBRIO | Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp |
| MANOPOLE | Specialized Trail Grips |
| FRENO ANT. | SRAM G2 RS, hydraulic disc, organic pads, G2 S4 4-piston caliper |
| FRENO POST. | SRAM G2 RS, hydraulic disc, organic pads, G2 S4 4-piston caliper |
| CAMBIO POST. | SRAM GX Eagle, 12-speed |
| COMANDI | SRAM GX Eagle, trigger, 12-speed |
| CASSETTA | SRAM GX Eagle, 12-speed, 10-50t |
| CATENA | SRAM NX Eagle, 12-speed |
| GUARNITURA | Truvativ STYLO, DUB |
| INGRANAGGI | Alloy, 32T |
| MOVIM. CENTR. | SRAM DUB, threaded BB |
| CERCHI | Roval Control Carbon, 25mm internal width, tubeless-ready |
| MOZZO ANT. | Specialized, sealed cartridge bearings, 15x110mm spacing, 28h |
| MOZZO POST. | DT Swiss 370, SRAM XD 3-pawl driver body, 12mm thru-axle, 148mm spacing, 28h |
| RAGGI | DT Swiss Industry |
| PNEUMATICO ANT. | Ground Control, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3" |
| PNEUMATICO POST. | Fast Trak, GRID casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3" |
| SELLA | Body Geometry Power Sport, hollow Cr-Mo rails |
| REGGISELLA | X-Fusion manic, 30.9mm, (S: 100mm, M-XL: 125mm) |

| ART. NR. | DESCRIZIONE | COLORE | MISURA |
|------------|---------------------------|--------------------------------|--------|
| 90320-3302 | EPIC EXPERT CARBON EVO 29 | Nero Satinato / Grigio Tortora | S |
| 90320-3303 | | | M |
| 90320-3304 | | | L |
| 90320-3305 | | | XL |