



Nero Satinato / Bianco



Rosso / Bianco Metallizzato

SPECIFICHE TECNICHE **Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

TELAIO	Specialized M5 Aluminum w/ D'Aluisio Smartweld Technology, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel
AMMORTIZZATORE	Custom RockShox Micro Brain shock w/ Spike Valve, AUTOSAG, 51x257mm
FORCELLA	RockShox Reba RL 29, Motion Control damper, 42mm offset, 15x110mm thru-axle, 100mm of travel
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Level TL, hydraulic disc
FRENO POST.	SRAM Level TL, hydraulic disc
CAMBIO POST.	SRAM NX Eagle, 12-speed
COMANDI	SRAM NX Eagle, trigger, 12-speed
CASSETTA	SRAM NX Eagle, 12-speed, 11-50t
CATENA	SRAM SX Eagle, 12-speed
GUARNITURA	Truvativ STYLO, DUB
INGRANAGGI	Steel, 30T
MOVIM. CENTR.	SRAM DUB, threaded BB
CERCHI	Roval Control Alloy 29", 25mm internal width
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 24h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power Sport, hollow Cr-Mo rails
REGGISELLA	Specialized, alloy, single-bolt, 30.9mm

EPIC COMP M5	XS	S	M	L	XL
Stack (mm)	588	588	602	616	630
Reach (mm)	388	408	433	456	475
Lunghezza tubo sterzo (mm)	95	95	110	125	140
Angolo Tubo Sterzo (°)	69,5	69,5	69,5	69,5	69,5
Altezza Mov. Centr. (mm)	332	332	332	332	332
BB Drop (mm)	38	38	38	38	38
Trail (mm)	94	94	94	94	94
Lunghezza Forcella (mm)	506	506	506	506	506
Offset Forcella/Rake (mm)	42	42	42	42	42
Avancorsa (mm)	639	659	689	717	742
Lunghezza Batticateni (mm)	438	438	438	438	438
Interasse (mm)	1075	1095	1125	1153	1178
Lunghezza Tubo Orizz. Virtuale (mm)	548	568	597	624	647
Altezza standover (mm)	765	765	768	771	775
Lunghezza piantone (mm)	385	400	434	470	520
Angolo Sella (°)	74,75	74,75	74,75	74,75	74,75
Larghezza Manubrio (mm)	750	750	750	750	750
Lunghezza attacco manubrio (mm)	60	60	70	80	90
Larghezza sella (mm)	155	155	143	143	143
Lunghezza reggisella (mm)	350	350	400	400	400
Lunghezza Pedivella (mm)	170	170	175	175	175

ART. NR.	DESCRIZIONE	COLORE	MISURA
90320-5201	EPIC COMP M5 29	Nero Satinato/ Bianco	XS
90320-5202			S
90320-5203			M
90320-5204			L
90320-5205			XL
90320-5002	EPIC COMP M5 29	Rosso / Bianco Metallizzato	S
90320-5003			M
90320-5004			L
90320-5005			XL