



Carbonio Satinato / Verde Quercia

EPIC COMP CARBON EVO	S	M	L	XL
Stack (mm)	595	605	619	638
Reach (mm)	398	423	446	465
Lunghezza Tubo sterzo (mm)	95	105	120	140
Angolo sterzo (degrees)	68.5	68.5	68.5	68.5
Altezza Mov. Centr. (mm)	340	340	340	340
BB Drop (mm)	32	32	32	32
Trail (mm)	99	99	99	99
Lunghezza intera forcella (mm)	526	526	526	526
Offset forcella / Rake (mm)	43	43	43	43
Avancorsa (mm)	667	695	723	749
Lunghezza Batticatena (mm)	438	438	438	438
Interasse (mm)	1103	1132	1159	1186
Lunghezza Tubo Orizz. virtuale (mm)	571	599	626	650
Altezza standover (mm)	772	777	782	804
Lunghezza piantone (mm)	400	434	470	520
Angolo Sella (degrees)	73.8	73.8	73.8	73.8
Lunghezza Pedivella (mm)	170	175	175	175
Larghezza Manubrio (mm)	750	750	750	750
Lunghezza attacco manubrio (mm)	60	70	70	80
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	361	411	411	411

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized FACT 11m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel
AMMORTIZZATORE	Custom RockShox Micro Brain shock w/ Spike Valve, AUTOSAG, 51x257mm
FORCELLA	RockShox Reba RL 29, Motion Control damper, 42mm offset, 15x110mm thru-axle, 120mm of travel
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Guide RS, hydraulic disc, organic pads, Guide S4 4-piston caliper
FRENO POST.	SRAM Guide RS, hydraulic disc, organic pads, Guide S4 4-piston caliper
CAMBIO POST.	SRAM NX Eagle, 12-speed
COMANDI	SRAM NX Eagle, trigger, 12-speed
CASSETTA	SRAM NX Eagle, 12-speed, 11-50t
CATENA	SRAM SX Eagle, 12-speed
GUARNITURA	Truvativ STYLO, DUB
INGRANAGGI	Steel, 32T
MOVIM. CENTR.	SRAM DUB, threaded BB
CERCHI	Roval Control Alloy 29", 25mm internal width
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 24h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Ground Control, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, GRID casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power Sport, hollow Cr-Mo rails
REGGISELLA	X-Fusion manic, 30.9mm, (S: 100mm, M-XL: 125mm)

ART. NR.	DESCRIZIONE	COLORE	MISURA
90320-5602	EPIC COMP EVO CARBON 29	Carbonio Satinato / Verde Quercia	S
90320-5603			M
90320-5604			L
90320-5605			XL