



Mirtillo / Menta

SIRRUS DISC DONNA	XS	S	M	L
Stack (mm)	537	556	581	593
Reach (mm)	372	373	383	400
Lunghezza Tubo sterzo (mm)	126	144	166	179
Angolo sterzo (degrees)	69,5	70	71	71
Altezza Mov. Centr. (mm)	275	275	275	275
BB Drop (mm)	70	70	70	70
Trail (mm)	75	72	65	65
Lunghezza intera forcella (mm)	390	390	390	390
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	605	608	617	638
Lunghezza Batticateni (mm)	440	440	440	440
Interasse (mm)	1036	1039	1047	1069
Lunghezza Tubo Orizz. virtuale (mm)	531	538	555	576
Altezza standover (mm)	690	715	745	775
Lunghezza piantone (mm)	345	380	425	455
Angolo Sella (degrees)	73.5	73.5	73.5	73.5
Lunghezza Pedivella (mm)	165	165	170	170
Larghezza Manubrio (mm)	580	580	600	600
Lunghezza attacco manubrio (mm)	70	80	90	100
Larghezza sella (mm)	155	155	155	155
Lunghezza reggisella (mm)	300	300	350	350

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully manipulated butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack/fender mounts
FORCELLA	Steel, 1-1/8" steerer, QR, flat-mount disc, Plug + Play rack & fender mounts
MANUBRIO	Double-buttressed alloy, 9-degree backsweep, 31.8mm
ATTACCO	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
SELLA	Specialized Aldia Sport, steel rails, 155mm
REGGISELLA	Alloy, 12mm offset, 2-bolt clamp, 27.2mm
FRENO ANT.	Promax F1, hydraulic disc, flat-mount, 160mm
FRENO POST.	Promax F1, hydraulic disc, flat-mount, 140mm
COMANDI	Shimano Acera, 8-speed
DERAGL. ANT.	Shimano Tourney, 3-speed, top-swing
CAMBIO POST.	Shimano Altus, 8-speed
CASSETTA	Shimano Altus, 8-speed, 11-32t
GUARNITURA	Shimano Tourney, TY501
INGRANAGGI	48/38/28T
MOVIM. CENTR.	BSA, 68mm, square taper
CATENA	KMC X8 w/ Missing Link™, 8-speed
CERCHI	700C disc, double-wall alloy, 22mm depth, 21mm internal width, disc-specific
MOZZO ANT.	Alloy, 6-bolt disc, loose ball bearing, quick-release, 32h
MOZZO POST.	Alloy, 6-bolt disc, 8-/9-speed freehub, loose ball bearing, quick-release, 32h
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Specialized Nimbus II Sport Reflect, 60TPI, wire bead w/ Black Belt protection, 700x32mm
PNEUMATICO POST.	Specialized Nimbus II Sport Reflect, 60TPI, wire bead w/ Black Belt protection, 700x32mm

ART. NR.	DESCRIZIONE	COLORE	MISURA
92918-7001	SIRRUS DONNA DISC	Mirtillo / Menta	XS
92918-7002			S
92918-7003			M
92918-7004			L