



Grigio Corazzata / Deserto Mojave

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized M5 Aluminum, 29 Trail HT Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing
FORCELLA	RockShox Recon RL 29, Solo Air, 51mm offset, 15x110mm thru-axle, XS/S: 100mm of travel, M/L/XL: 120mm of travel
ATTACCO	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
MANUBRIO	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, XS 720mm, S-XL 750mm, 31.8mm clamp
MANOPOLE	Specialized Body Geometry XC, clamp-on
FRENO ANT.	Shimano BR-MT200, hydraulic disc, 180mm
FRENO POST.	Shimano BR-MT200, hydraulic disc, 180mm
CAMBIO POST.	Shimano Deore, Shadow Plus, GS cage, 10-speed
COMANDI	Shimano Deore, 10-speed
CASSETTA	Shimano HG500, 10-speed, 11-42t
CATENA	KMC X10eT, 10-speed w/ Missing Link™
GUARNITURA	Custom alloy forged crankarms
INGRANAGGI	32T, steel
CERCHI	Specialized XC 29, 25mm internal width, disc-specific
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 28h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Ground Control, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Ground Control, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Myth 155 XS, Body Geometry Henge 143 S/M/L/XL, steel rails
REGGISELLA	Specialized 2-bolt head, forged alloy, 8mm offset, micro-adjust, 30.9mm
MOTORE	Specialized 1.3, custom Rx Trail-tuned motor, 250W nominal
UI/REMOTE	Specialized Handlebar Trail Remote w/walk-assist
BATTERIA	Specialized M1-500, integrated Trail Display, ANT+/Bluetooth® module, 500Wh
CARICATORE	Custom charger, 42V4A w/ Rosenberger plug
CABLAGGIO	Custom Specialized wiring harness
SWAT	Specialized Z-Cage w/EMT Cage Mount MTB Tool

TURBO LEVO HARDTAIL COMP 29 M5

	S	M	L	XL
Lunghezza piantone c/f (mm)	394	434	470	505
Lunghezza Tubo Orizz. virtuale (mm)	574	608	633	655
BB Drop (mm)	55	55	55	55
Altezza Mov. Centr. (mm)	308	308	308	308
Lunghezza Batticateni (mm)	450	450	450	450
Angolo Sella effettivo (degrees)	74	73	73	73
Angolo sterzo (degrees)	67	67	67	67
Interasse (mm)	1140	1164	1190	1213
Altezza standover (mm)	756	786	812	838
Lunghezza Tubo sterzo (mm)	110	100	115	130
Stack (mm)	607	616	630	644
Reach (mm)	400	420	440	458
Lunghezza intera forcella (mm)	510	530	530	530

ART. NR.	DESCRIZIONE	COLORE	MISURA
95120-5202	TURBO LEVO HT COMP 29 M5	Grigio Corazzata Deserto/Mojave	S
95120-5203			M
95120-5204			L
95120-5205			XL