

TURBO LEVO HARDTAIL M5



Nero



Verde Quercia / Verde Abete Fluo

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized M5 Aluminum, 29 Trail HT Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing
FORCELLA	SR Suntour XCM32, 47mm offset, 15x110mm thru-axle, 100mm travel
ATTACCO	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
MANUBRIO	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, XS 720mm, S-XL 750mm, 31.8mm clamp
MANOPOLE	Specialized Body Geometry XC, clamp-on
FRENO ANT.	Shimano BR-MT200, hydraulic disc, 180mm
FRENO POST.	Shimano BR-MT200, hydraulic disc, 180mm
CAMBIO POST.	Shimano Alivio, Shadow Design, SGS cage, 9-speed
COMANDI	Shimano Alivio, 9-speed w/ Optical Gear Display
CASSETTA	Shimano HG201, 9-speed, 11-36t
CATENA	KMC e9S.NPBK, e-bike chain, 9-speed w/ Missing Link™
GUARNITURA	2D cold-forged alloy, custom offset, 165mm
INGRANAGGI	32T, steel ring
CERCHI	Specialized XC 29, 25mm internal width, disc-specific
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Ground Control, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Ground Control, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Myth 155 XS, Body Geometry Henge 143 S/M/L/XL, steel rails
REGGISELLA	Specialized 2-bolt head, forged alloy, 8mm offset, micro-adjust, 30.9mm
MOTORE	Specialized 1.2 E, custom Rx Street-tuned motor, 250W nominal
UI/REMOTE	Specialized Handlebar Trail Remote w/walk-assist
BATTERIA	Specialized M1-400, integrated Trail Display, ANT+/Bluetooth® module, 400Wh
CARICATORE	Custom Specialized 42V2A Charger w/ Rosenberger plug, AC power cord included
CABLAGGIO	Custom Specialized wiring harness
SWAT	Specialized Z-Cage w/EMT Cage Mount MTB Tool

TURBO LEVO HARDTAIL M5	XS	S	M	L	XL
Lunghezza piantone c/f (mm)	390	394	434	470	505
Lunghezza Tubo Orizz. virtuale (mm)	568	574	608	633	655
BB Drop (mm)	55	55	55	55	55
Altezza Mov. Centr. (mm)	308	308	308	308	308
Lunghezza Batticatenina (mm)	450	450	450	450	450
Angolo Sella effettivo (degrees)	74	74	73	73	73
Angolo sterzo (degrees)	67	67	67	67	67
Interasse (mm)	1121	1140	1164	1190	1213
Altezza standover (mm)	688	756	786	812	838
Lunghezza Tubo sterzo (mm)	100	110	100	115	130
Stack (mm)	598	607	616	630	644
Reach (mm)	385	400	420	440	458
Lunghezza intera forcella (mm)	510	510	530	530	530

ART. NR.	DESCRIZIONE	COLORE	MISURA
95120-7301	LEVO HT 29 M5	Nero	XS
95120-7302			S
95120-7303			M
95120-7304			L
95120-7305			XL
95120-7402	LEVO HT 29 M5	Verde Quercia / Verde Abete Fluo	S
95120-7403			M
95120-7404			L
95120-7405			XL