



Carbonio / Cromo



Grigio Tortora / Rosso Rocket

S-WORKS TURBO LEVO	S	M	L	XL
Stack (mm)	606	606	634	647
Reach (mm)	415	435	455	480
Lunghezza Tubo sterzo (mm)	95	95	125	140
Angolo sterzo (degrees)	66.04	66.04	66.04	66.04
Altezza Mov. Centr. (mm)	347.5	347.5	347.5	347.5
BB Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Lunghezza intera forcella (mm)	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	729	749	781	812
Lunghezza Batticatena (mm)	455	455	455	455
Interasse (mm)	1182	1202	1235	1266
Lunghezza Tubo Orizz. virtuale (mm)	577	600	631	664
Altezza standover (mm)	760	760	781	787
Lunghezza piantone (mm)	380	410	455	505
Angolo Sella (degrees)	75.04	74.79	74.48	74.14
Lunghezza Pedivella (mm)	165	165	165	165
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	50	50	50	50
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	125	150	170	170

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

TELAIO	S-Works FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	FOX FLOAT DPS Factory, Kashima coating, 3-position adjustment, 52.5x210mm, Rx Trail Tune
FORCELLA	FOX FLOAT Factory, 36, GRIP2 damper, 51mm offset, 15x110mm, tapered alloy steerer, Kashima, 150mm of travel
ATTACCO	Deity Copperhead, 32.8mm, 50mm
MANUBRIO	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 31.8mm
MANOPOLE	Specialized Sip grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRENO ANT.	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
CAMBIO POST.	SRAM XX1, 11-speed
COMANDI	SRAM XO1, single-click lever
CASSETTA	SRAM XG1199, XD, 11-speed, 10-42t
CATENA	SRAM XX1, 11-speed
GUARNITURA	Praxis, full carbon ISIS, custom offset, 165mm
INGRANAGGI	32T, custom steel
CERCHI	Roval Traverse SL 29, hookless carbon, 30mm inner width, 2Bliss Ready, hand-built, 28h
MOZZO ANT.	Roval Traverse SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing
MOZZO POST.	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing
RAGGI	DT Competition Race
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"
PNEUMATICO POST.	Eliminator, BLCK DMND Casing, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Myth 155 S, Body Geometry Henge 143 M/L/XL, hollow ti rails
REGGISELLA	RockShox Reverb AXS, 30.9mm, S: 125, M:150, L/XL: 170mm
MOTORE	Specialized 2.1, custom Rx Trail-tuned motor, 250W nominal
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized M2-700, integrated battery w/rock guard, 700Wh
CARICATORE	Custom charger, 42V4A w/ Rosenberger plug
CABLAGGIO	Custom Specialized wiring harness
SWAT	Specialized Z-Cage, Swat CC Multitool in steerer tube with Chaintool

ART. NR.	DESCRIZIONE	COLORE	MISURA
95220-0202	LEVO SW CARBON 29 NB	Carbonio / Cromo	S
95220-0203			M
95220-0204			L
95220-0205			XL
95220-0302	LEVO SW CARBON 29 NB	Grigio Tortora / Rosso Rocket	S
95220-0303			M
95220-0304			L
95220-0305			XL