



Blu Navy / Bianco / Nero



Nero / Lilla



Rosso Vivo / Nero

TURBO LEVO M5	S	M	L	XL
Stack (mm)	606	606	634	647
Reach (mm)	415	435	455	480
Lunghezza Tubo sterzo (mm)	95	95	125	140
Angolo sterzo (degrees)	66.04	66.04	66.04	66.04
Altezza Mov. Centr. (mm)	347.5	347.5	347.5	347.5
BB Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Lunghezza intera forcella (mm)	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	729	749	781	812
Lunghezza Batticatena (mm)	455	455	455	455
Interasse (mm)	1182	1202	1235	1266
Lunghezza Tubo Orizz. virtuale (mm)	577	600	631	664
Altezza standover (mm)	760	760	781	787
Lunghezza piantone (mm)	380	410	455	505
Angolo Sella (degrees)	75.04	74.79	74.48	74.14
Lunghezza Pedivella (mm)	165	165	165	165
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	45	45	45	45
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	406	456	456	456

SPECIFICHE TECNICHE

	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Specialized M5 Premium Aluminum, 29 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	RockShox Deluxe Select w/ custom air valve, 52.5x210mm
FORCELLA	RockShox 35 29, DebonAir spring, Motion Control damper, 51mm offset, 15x110mm thru-axle
ATTACCO	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 780mm, 31.8mm clamp
MANOPOLE	Specialized Sip grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRENO ANT.	SRAM Level T hydraulic disc, 4-Piston Caliper, 200mm
FRENO POST.	SRAM Level T hydraulic disc, 2-Piston Caliper, 200mm
CAMBIO POST.	SRAM NX, 11-speed
COMANDI	SRAM S700, single-click lever
CASSETTA	SRAM PG-1130, 11-speed, 11-42t
CATENA	KMC X11ET, 11-speed w/ Missing Link™
GUARNITURA	Praxis, 2D cold-forged alloy, custom offset, 165mm
INGRANAGGI	32T, custom steel
CERCHI	Roval Traverse 29, hookless alloy, 30mm inner width, tubeless ready
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 28h
MOZZO POST.	Specialized Turbo, sealed cartridge bearings, 12x148mm thru-axle, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"
PNEUMATICO POST.	Eliminator, BLCK DMND Casing, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Myth 155 S, Body Geometry Henge 143 M/L/XL, steel rails
REGGISELLA	TranzX dropper, 34.9mm, XS-S: 100mm, M: 120mm, L/XL: 150mm Travel
MOTORE	Specialized 2.1, custom Rx Trail-tuned motor, 250W nominal
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized M2-500, integrated battery w/rock guard, 500Wh
CARICATORE	Custom charger, 42V4A w/ Rosenberger plug
CABLAGGIO	Custom Specialized wiring harness
SWAT	Specialized Z-Cage w/EMT Cage Mount MTB Tool

ART. NR.	DESCRIZIONE	COLORE	MISURA
95220-7502	LEVO 29 NB	Blu Navy / Bianco / Nero	S
95220-7503			M
95220-7504			L
95220-7505			XL
95220-7302	LEVO 29 NB	Nero / Lilla	S
95220-7303			M
95220-7304			L
95220-7305			XL
95220-7402	LEVO 29 NB	Rosso Vivo / Nero	S
95220-7403			M
95220-7404			L
95220-7405			XL