

KENEVO EXPERT



Verde Salvia / Abete



Nero con Kit Decalco

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

| | |
|------------------|--|
| TELAIO | Specialized M5 Premium Aluminum, 27.5 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 180mm of travel |
| AMMORTIZZATORE | RockShox Super Deluxe Coil Select, 62.5x230mm, S2: 450lb, S3: 500lb, S4: 550lb, S5: 600lb |
| FORCELLA | RockShox Boxxer Select RC, 27.5, DebonAir, 20x110mm Boost™, 35mm chassis, 180mm of travel |
| ATTACCO | Specialized Direct Mount DH Stem, two-piece, forged alloy, 45mm |
| MANUBRIO | Specialized, 7050 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 800mm width |
| MANOPOLE | Specialized Sip grip, half-waffle, S/M: regular thickness, L/XL: XL thickness |
| FRENO ANT. | SRAM Code R, 4-piston caliper, hydraulic disc, 200mm |
| FRENO POST. | SRAM Code R, 4-piston caliper, hydraulic disc, 200mm |
| CAMBIO POST. | SRAM GX, long cage, 11-speed |
| COMANDI | SRAM S700, single-click lever |
| CASSETTA | SRAM PG-1130, 11-speed, 11-42t |
| CATENA | KMC X11ET, 11-speed w/ Missing Link™ |
| GUARNITURA | Praxis, 2D cold-forged alloy, custom offset, 165mm |
| INGRANAGGI | 32T, custom steel |
| CERCHI | Roval 27.5" Alloy DH, 28mm internal width, 32h |
| MOZZO ANT. | Specialized, sealed cartridge bearings, 15x110mm spacing, 32h |
| MOZZO POST. | DT Swiss 370, 6-bolt, 12x148mm thru-axle, 32h |
| RAGGI | DT Swiss Industry |
| PNEUMATICO ANT. | Butcher, BLCK DMND casing, 2Bliss Ready, 27.5 x 2.6" |
| PNEUMATICO POST. | Butcher, BLCK DMND casing, 2Bliss Ready, 27.5 x 2.6" |
| SELLA | Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm |
| REGGISELLA | Command Post IRcc, 16-position micro-height adjustable, two-bolt head, bottom mount cable routing, remote SRL lever, 34.9mm, S: 130mm, M/L/XL: 160mm of travel |
| MOTORE | Specialized 2.1, custom Rx Trail-tuned motor, 250W nominal |
| UI/REMOTE | Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth® |
| BATTERIA | Specialized M2-700, integrated battery w/rock guard, 700Wh |
| CARICATORE | Custom charger, 42V4A w/ Rosenberger plug |
| CABLAGGIO | Custom Specialized wiring harness |
| SWAT | Specialized Z-Cage w/EMT Cage Mount MTB Tool |

| KENEVO EXPERT | S2 | S3 | S4 | S5 |
|-------------------------------------|------|------|------|------|
| Stack (mm) | 605 | 614 | 623 | 632 |
| Reach (mm) | 445 | 470 | 495 | 520 |
| Lunghezza Tubo sterzo (mm) | 105 | 115 | 125 | 135 |
| Angolo sterzo (degrees) | 64 | 64 | 64 | 64 |
| Altezza Mov. Centr. (mm) | 345 | 345 | 345 | 345 |
| BB Drop (mm) | 14 | 14 | 14 | 14 |
| Trail (mm) | 128 | 128 | 128 | 128 |
| Lunghezza intera forcella (mm) | 572 | 572 | 572 | 572 |
| Offset forcella / Rake (mm) | 42 | 42 | 42 | 42 |
| Avancorsa (mm) | 780 | 809 | 839 | 868 |
| Lunghezza Batticateni (mm) | 454 | 454 | 454 | 454 |
| Interasse (mm) | 1234 | 1263 | 1293 | 1322 |
| Lunghezza Tubo Orizz. virtuale (mm) | 585 | 612 | 639 | 666 |
| Altezza standover (mm) | 794 | 794 | 794 | 794 |
| Lunghezza piantone (mm) | 400 | 420 | 440 | 465 |
| Angolo Sella (degrees) | 77 | 77 | 77 | 77 |
| Lunghezza Pedivella (mm) | 165 | 165 | 165 | 165 |
| Larghezza Manubrio (mm) | 800 | 800 | 800 | 800 |
| Lunghezza attacco manubrio (mm) | 45 | 45 | 45 | 45 |
| Larghezza sella (mm) | 143 | 143 | 143 | 143 |
| Lunghezza reggisella (mm) | 369 | 429 | 429 | 429 |

| ART. NR. | DESCRIZIONE | COLORE | MISURA |
|------------|--------------------------|----------------------|--------|
| 98020-3302 | KENEVO EXPERT 6FATTIE NB | Verde Salvia / Abete | S2 |
| 98020-3303 | | | S3 |
| 98020-3304 | | | S4 |
| 98020-3305 | | | S5 |
| 98020-3202 | KENEVO EXPERT 6FATTIE NB | Nero con Kit Decalco | S2 |
| 98020-3203 | | | S3 |
| 98020-3204 | | | S4 |
| 98020-3205 | | | S5 |