



Grigio Tortora / Rosso Rocket

Canna di Fucile / Fluo

KENEVO COMP	S2	S3	S4	S5
Stack (mm)	605	614	623	632
Reach (mm)	445	470	495	520
Lunghezza Tubo sterzo (mm)	105	115	125	135
Angolo sterzo (degrees)	64	64	64	64
Altezza Mov. Centr. (mm)	345	345	345	345
BB Drop (mm)	14	14	14	14
Trail (mm)	128	128	128	128
Lunghezza intera forcella (mm)	572	572	572	572
Offset forcella / Rake (mm)	42	42	42	42
Avancorsa (mm)	780	809	839	868
Lunghezza Batticateni (mm)	454	454	454	454
Interasse (mm)	1234	1263	1293	1322
Lunghezza Tubo Orizz. virtuale (mm)	585	612	639	666
Altezza standover (mm)	794	794	794	794
Lunghezza piantone (mm)	400	420	440	465
Angolo Sella (degrees)	77	77	77	77
Lunghezza Pedivella (mm)	165	165	165	165
Larghezza Manubrio (mm)	800	800	800	800
Lunghezza attacco manubrio (mm)	45	45	45	45
Larghezza sella (mm)	143	143	143	143
Lunghezza reggisella (mm)	375	438	438	438

## SPECIFICHE TECNICHE

**Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.**

TELAIO	Specialized M5 Premium Aluminum, 27.5 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 180mm of travel
AMMORTIZZATORE	Marzocchi Bomber CR, 62.5x230mm, S2: 450lb, S3: 500lb, S4: 550lb, S5: 600lb
FORCELLA	Marzocchi Bomber Z1, 27.5, Boost™ 15x110mm, 36mm chassis, FIT GRIP damper, 180mm of travel
ATTACCO	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized, 7050 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 800mm width
MANOPOLE	Specialized Sip grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRENO ANT.	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	SRAM Code R, 4-piston caliper, hydraulic disc, 200mm
CAMBIO POST.	SRAM NX, 11-speed
COMANDI	SRAM S700, single-click lever
CASSETTA	SRAM PG-1130, 11-speed, 11-42t
CATENA	KMC X11ET, 11-speed w/ Missing Link™
GUARNITURA	Praxis, 2D cold-forged alloy, custom offset, 165mm
INGRANAGGI	32T, custom steel
CERCHI	Roval 27.5" Alloy DH, 28mm internal width, 32h
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm spacing, 32h
MOZZO POST.	Specialized Turbo, sealed cartridge bearings, 12x148mm thru-axle, 32h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Butcher, BLCK DMND casing, 2Bliss Ready, 27.5 x 2.6"
PNEUMATICO POST.	Butcher, BLCK DMND casing, 2Bliss Ready, 27.5 x 2.6"
SELLA	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
MOTORE	Specialized 2.1, custom Rx Trail-tuned motor, 250W nominal
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized M2-500, integrated battery w/rock guard, 500Wh
CARICATORE	Custom charger, 42V4A w/ Rosenberger plug
CABLAGGIO	Custom Specialized wiring harness
SWAT	Specialized Z-Cage w/EMT Cage Mount MTB Tool

ART. NR.	DESCRIZIONE	COLORE	MISURA
98020-5302	KENEVO COMP 6FATTIE NB	Canna di Fucile / Fluo	S2
98020-5303			S3
98020-5304			S4
98020-5305			S5
98020-5202	KENEVO COMP 6FATTIE NB	Grigio Tortora / Rosso Rocket	S2
98020-5203			S3
98020-5204			S4
98020-5205			S5