

S-WORKS TURBO LEVO SL



Carbonio / Nero / Cromo

La Turbo Levo SL è una nuova, leggera eMTB che replica la guida veloce e vivace delle nostre Stumpjumper... aggiungendo appena quel pizzico di potenza, quella piccola spinta in più. Il modello top di gamma S-Works Levo SL ha un telaio completamente in fibra di carbonio, sospensioni FOX Factory e trasmissione SRAM Eagle XX1.

- La Levo SL assomiglia molto alla Stumpjumper e non a caso, sul trail, si pedala allo stesso modo. Il nostro obiettivo era di creare uno Stumpjumper con quella piccola spinta in più - un telaio asimmetrico con la giusta rigidità e 150mm di escursione sia anteriore che posteriore, realizzato interamente in fibra di carbonio FACT 11m.
- Il leggero motore SL 1.1 raddoppierà i tuoi sforzi grazie ai 240 watt di assistenza. La curva di erogazione del motore fornisce potenza perfettamente in linea con la tua normale cadenza e non dà resistenza se pedali senza assistenza.
- Hai paura che finisca la batteria? Non con la Levo SL che 'si divora' le lunghe giornate in sella. Il range extender aumenterà l'autonomia del 50%. La Mission Control App potrà gestire le batterie in modo da farli durare quanto serve.
- -

S-WORKS TURBO LEVO SL	S	M	L	XL
Stack (mm)	606	606	633	647
Reach (mm)	415	435	455	480
Lunghezza Tubo sterzo (mm)	95	95	125	140
Angolo sterzo (degrees)	66	66	66	66
Altezza movimento centrale (mm)	348	348	348	348
BB Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Lunghezza Forcella (mm)	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	729	749	781	812
Lunghezza Batticateni (mm)	437	437	437	437
Interasse (mm)	1165	1185	1217	1248
Lunghezza Tubo Orizz. virtuale (mm)	574	597	629	663
Altezza standover (mm)	787	790	807	814
Lunghezza piantone (mm)	390	410	455	505
Angolo Sella (degrees)	75.3	75	74.6	74.2
Lunghezza Pedivella (mm)	165	165	170	170
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	40	40	50	50
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	125	150	170	170

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	FOX FLOAT DPS Factory, Kashima coating, 3-position adjustment, 52.5x210mm, Rx Trail Tune
FORCELLA	FOX Factory 34 FLOAT 29, Kashima Coating, FIT4 damper, 51mm offset, 3-position adjustment, 15x110mm, tapered alloy steerer, 150mm of travel
ATTACCO	Syntace MegaForce 2, 6-degree, 31.8mm clamp
MANUBRIO	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 31.8mm
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM G2 ULTIMATE, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	SRAM G2 ULTIMATE, 4-piston caliper, hydraulic disc, 180mm
CAMBIO POST.	SRAM XX1 Eagle, 12-speed
COMANDI	SRAM XX1 Eagle, trigger, 12-speed
CASSETTA	SRAM XG-1299 Eagle, 10-50t
CATENA	SRAM XX1 Eagle, 12-speed
GUARNITURA	Praxis, carbon M30, custom offset
INGRANAGGI	SRAM X-Sync Eagle, 94 BCD, 30T
CERCHI	Roval Traverse SL 29, hookless carbon, 30mm inner width, 2Bliss Ready, hand-built, 28h
MOZZO ANT.	Roval Traverse SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 28h
MOZZO POST.	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Competition Race
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Bridge, 155/143mm, Hollow Ti-rails
REGGISELLA	RockShox Reverb AXS, 30.9mm, S: 125, M:150, L/XL: 170mm
MOTORE	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized SL1-320, fully integrated, 320Wh; also included a Specialized SL1-160, external battery w/Cable, 160Wh
CARICATORE	Custom charger, 48V System w/ SL system charger plug
CABLAGGIO	Custom Specialized wiring harness w/ chargeport
SWAT	Specialized Z-Cage, Swat CC Multitool in steerer tube w/ Chaintool

ART. NR.	DESCRIZIONE	COLORE	MISURA
96820-0002	LEVO SL SW CARBON	Carbonio / Nero / Cromo	S
96820-0003			M
96820-0004			L
96820-0005			XL