

# EPIC EVO S-WORKS



Quercia Lucido Metallizzato/Polvere di diamante

EPIC EVO S-WORKS	S	M	L	XL
Stack (mm)	593	597	611	629
Reach (mm)	406	436	460	485
Lunghezza Tubo sterzo (mm)	95	100	115	135
Angolo sterzo (degrees)	66.5	66.5	66.5	66.5
Altezza Mov. Centr. (mm)	336	336	336	336
BB Drop (mm)	36	36	36	36
Trail (mm)	114	114	114	114
Lunghezza intera forcella (mm)	530	530	530	530
Offset forcella / Rake (mm)	44	44	44	44
Avancorsa (mm)	697	729	759	792
Lunghezza Batticateni (mm)	438	438	438	438
Interasse (mm)	1132	1164	1194	1227
Altezza standover (mm)	779	781	793	804
Lunghezza piantone (mm)	400	430	470	520
Angolo Sella (degrees)	74.8	74.5	74.5	74.5
Lunghezza Pcdivella (°)	170	175	175	175
Larghezza Manubrio (mm)	760	760	760	760
Lunghezza attacco manubrio (°)	60	60	60	60
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (°)	125	125	150	150

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	S-Works FACT 12m Carbon, Progressive XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 110mm of travel
AMMORTIZZATORE	RockShox SID LUXE ULTIMATE, Rx XC Tune, Two Position, Rebound Adjust, 190x40mm
FORCELLA	Rockshox SID ULTIMATE, Charger Race Day Damper, Debon Air, 15x110mm, 44mm offset, 120mm Travel
ATTACCO	S-Works SL, alloy, titanium bolts, 6-degree rise
MANUBRIO	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM G2 Ultimate, 4-piston caliper, hydraulic disc
FRENO POST.	SRAM G2 Ultimate, 4-piston caliper, hydraulic disc
CAMBIO POST.	SRAM XX1 Eagle AXS
COMANDI	SRAM AXS Eagle Controller
CASSETTA	SRAM XG-1299 Eagle, 10-50t
CATENA	SRAM XX1 Eagle
GUARNITURA	SRAM XX1 Eagle, Boost™ 148, DUB, 170/175mm
INGRANAGGI	SRAM Eagle Alloy, 32T, Direct Mount
MOVIM. CENTR.	SRAM DUB, BSA 73mm, Threaded
CERCHI	Roval Control SL, Carbon offset design, 29mm internal width, 4mm hook width, Tubeless ready, 24h
MOZZO ANT.	Roval Control SL, DT Swiss Internals, Ceramic Bearings, 6-bolt, 15mm thru-axle, 110mm spacing, Torque caps, 24h straight pull t-head
MOZZO POST.	Roval Control SL, DT Swiss 180 Internals, DT Swiss Ratchet EXP, Ceramic bearings, 12mm thru-axle, 148mm spacing, 24h
RAGGI	DT Swiss Aerolite T-head
PNEUMATICO ANT.	Ground Control, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry S-Works Power, carbon fiber rails, carbon fiber base, 143mm
REGGISELLA	RockShox Reverb AXS, 30.9, 1X remote, (SM:100mm, M: 125mm, L-XL: 150mm travel)

ART. NR.	DESCRIZIONE	COLORE	MISURA
94820-0002	EPIC EVO SW	Quercia Lucido Metallizzato/ Polvere di diamante	S
94820-0003			M
94820-0004			L
94820-0005			XL