

EPIC EVO EXPERT



Blu satinato/Azzurrino

EPIC EVO EXPERT	XS	S	M	L	XL
Stack (mm)	603	593	597	611	629
Reach (mm)	380	406	436	460	485
Lunghezza Tubo sterzo (mm)	95	95	100	115	135
Angolo sterzo (degrees)	66.5	66.5	66.5	66.5	66.5
Altezza Mov. Centr. (mm)	326	336	336	336	336
BB Drop (mm)	46	36	36	36	36
Trail (mm)	114	114	114	114	114
Lunghezza intera forcella (mm)	530	530	530	530	530
Offset forcella / Rake (mm)	44	44	44	44	44
Avancorsa (mm)	672	697	729	759	792
Lunghezza Batticateni (mm)	438	438	438	438	438
Interasse (mm)	1106	1132	1164	1194	1227
Altezza standover (mm)	760	779	781	793	804
Lunghezza piantone (mm)	375	400	430	470	520
Angolo Sella (degrees)	75.5	74.8	74.5	74.5	74.5
Lunghezza Peditivella (mm)	165	170	175	175	175
Larghezza Manubrio (mm)	750	750	750	750	750
Lunghezza attacco manubrio (mm)	60	60	60	60	60
Larghezza sella (mm)	155	155	143	143	143
Lunghezza reggisella (mm)	310	361	361	425	425

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	FACT 11m Full Carbon, Progressive XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 110mm of travel
SWAT	SWAT EMT Cage-Mount Tool
AMMORTIZZATORE	RockShox SID LUXE Select+, Rx XC Tune, Two Position, Rebound Adjust, 190x40mm
FORCELLA	Rockshox SID Select+, Charger 2 RL Damper, Debon Air, 15x110mm, 44mm offset, 120mm Travel
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM G2 RS, 4-piston caliper, hydraulic disc
FRENO POST.	SRAM G2 RS, 4-piston caliper, hydraulic disc
CAMBIO POST.	SRAM X01 Eagle, 12-speed
COMANDI	SRAM X01 Eagle, trigger, 12-speed
CASSETTA	SRAM XG-1275 Eagle, 12-speed, 10-50t
CATENA	SRAM GX Eagle, 12-speed
GUARNITURA	SRAM X1 Eagle, DUB, 32t, XS: 165mm, SM: 170mm, M-XL: 175mm
INGRANAGGI	SRAM Eagle Alloy 32T Direct mount
MOVIM. CENTR.	SRAM DUB, BSA 73mm, Threaded
CERCHI	Roval Control Carbon, 25mm internal width, Zero bead hook, Tubeless ready, 28h
MOZZO ANT.	DT Swiss 350, 15x110mm spacing, Torque caps, 6-bolt, 28h
MOZZO POST.	DT Swiss 350, Star Ratchet, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Competition Race
PNEUMATICO ANT.	Ground Control, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power Sport, hollow Cr-Mo rails
REGGISELLA	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, XS-SM: 100mm travel, M: 125mm travel, L-XL: 150mm travel

ART. NR.	DESCRIZIONE	COLORE	MISURA
94820-3101	EPIC EVO EXPERT	Blu satinato/Azzurrino	XS
94820-3102			S
94820-3103			M
94820-3104			L
94820-3105			XL