



Carbonio Satinato/Olografico



Rosso Lucido/Bianco perlato

EPIC EXPERT	XS	S	M	L	XL
Stack (mm)	596	586	591	605	623
Reach (mm)	390	415	445	470	495
Lunghezza Tubo sterzo (mm)	95	95	100	115	135
Angolo sterzo (degrees)	67.5	67.5	67.5	67.5	67.5
Altezza Mov. Centr. (mm)	314	324	324	324	324
BB Drop (mm)	58	48	48	48	48
Trail (mm)	106	106	106	106	106
Lunghezza intera forcella (mm)	505	505	505	505	505
Offset forcella / Rake (mm)	44	44	44	44	44
Avancorsa (mm)	663	687	719	750	782
Lunghezza Batticateni (mm)	433	433	433	433	433
Interasse (mm)	1090	1116	1148	1179	1211
Altezza standover (mm)	740	763	766	776	788
Lunghezza piantone (mm)	375	400	430	470	520
Angolo Sella (degrees)	76.5	75.8	75.5	75.5	75.5
Lunghezza Peditivella (mm)	165	170	175	175	175
Larghezza Manubrio (mm)	750	750	750	750	750
Lunghezza attacco manubrio (mm)	60	60	70	70	70
Larghezza sella (mm)	155	155	143	143	143
Lunghezza reggisella (mm)	350	350	400	400	400

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	FACT 11m Full Carbon, Modern XC Race Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel
SWAT	SWAT EMT Cage-Mount Tool
AMMORTIZZATORE	RockShox-Specialized BRAIN, Rx XC Tune, 5 Position Platform Adjust, Rebound Adjust, Integrated Extension, 265x52.5mm
FORCELLA	RockShox SID SL BRAIN, Bottom-Adjust Brain damper, Debon Air, 15x110mm, 44mm offset, 100mm Travel
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Level TL, 2-piston caliper, hydraulic disc
FRENO POST.	SRAM Level TL, 2-piston caliper, hydraulic disc
CAMBIO POST.	SRAM X01 Eagle, 12-speed
COMANDI	SRAM X01 Eagle, trigger, 12-speed
CASSETTA	SRAM XG-1275 Eagle, 12-speed, 10-50t
CATENA	SRAM GX Eagle, 12-speed
GUARNITURA	SRAM X1 Eagle, DUB, 32t, XS: 165mm, SM: 170mm, M-XL: 175mm
INGRANAGGI	SRAM Eagle Alloy 32T Direct mount
MOVIM. CENTR.	SRAM DUB, BSA 73mm, Threaded
CERCHI	Roval Control Carbon, 25mm internal width, Zero bead hook, Tubeless ready, 28h
MOZZO ANT.	DT Swiss 350, 15x110mm spacing, Torque caps, 6-bolt, 28h
MOZZO POST.	DT Swiss 350, Star Ratchet, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Competition Race
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power Sport, hollow Cr-Mo rails
REGGISELLA	Specialized Alloy, Single Bolt, 30.9mm

ART. NR.	DESCRIZIONE	COLORE	MISURA
97620-3201	EPIC EXPERT	Carbonio Satinato/Olografico	XS
97620-3202			S
97620-3203			M
97620-3204			L
97620-3205			XL
97620-3002	EPIC EXPERT	Rosso Lucido/Bianco perlato	S
97620-3003			M
97620-3004			L
97620-3005			XL