



Petrolio Satinato Cangiante/Argento



Rosso Lucido Perlato/Bianco Metallizzato

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

TELAIO	FACT 11m Full Carbon, Modern XC Race Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel
SWAT	SWAT EMT Cage-Mount Tool
AMMORTIZZATORE	RockShox-Specialized BRAIN, Rx XC Tune, 5 Position Platform Adjust, Rebound Adjust, Integrated Extension, 265x52.5mm
FORCELLA	RockShox Reba RL, Motion Control damper, Solo Air, 42mm offset, 15x110mm thru-axle, 100mm of travel
ATTACCO	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Alloy Minirise, 10mm rise, 750mm, 31.8mm clamp
MANOPOLE	Specialized Trail Grips
FRENO ANT.	Shimano SLX M7100, 2-piston caliper, hydraulic disc
FRENO POST.	Shimano SLX M7100, 2-piston caliper, hydraulic disc
CAMBIO POST.	Shimano SLX M7100, SGS, 12-speed
COMANDI	Shimano SLX, M7100, 12spd
CASSETTA	Shimano SLX, CS-M7100, 12-speed, 10-51t
CATENA	Shimano SLX, M7100, 12-speed
GUARNITURA	Shimano SLX 7100, Hollowtech 2, 32t Chainring, XS: 165mm, SM: 170mm, M-XL: 175mm
INGRANAGGI	32T
MOVIM. CENTR.	Shimano, BB52, Threaded
CERCHI	Specialized Alloy, Tubeless Ready, 25mm internal width, 28h
MOZZO ANT.	Shimano MT400-B, Centerlock 28h, 15x110 Boost
MOZZO POST.	Shimano MT510-B, Centerlock 28h, 12x148 Boost, Microspline
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
PNEUMATICO POST.	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Power Sport, hollow Cr-Mo rails
REGGISELLA	Specialized Alloy, Single Bolt, 30.9mm

EPIC COMP	XS	S	M	L	XL
Stack (mm)	596	586	591	605	623
Reach (mm)	390	415	445	470	495
Lunghezza Tubo sterzo (mm)	95	95	100	115	135
Angolo sterzo (degrees)	67.5	67.5	67.5	67.5	67.5
Altezza Mov. Centr. (mm)	314	324	324	324	324
BB Drop (mm)	58	48	48	48	48
Trail (mm)	106	106	106	106	106
Lunghezza intera forcella (mm)	505	505	505	505	505
Offset forcella / Rake (mm)	44	44	44	44	44
Avancorsa (mm)	663	687	719	750	782
Lunghezza Batticateni (mm)	433	433	433	433	433
Interasse (mm)	1090	1116	1148	1179	1211
Altezza standover (mm)	740	763	766	776	788
Lunghezza piantone (mm)	375	400	430	470	520
Angolo Sella (degrees)	76.5	75.8	75.5	75.5	75.5
Lunghezza Peditivella (mm)	165	170	175	175	175
Larghezza Manubrio (mm)	750	750	750	750	750
Lunghezza attacco manubrio (mm)	60	60	70	70	70
Larghezza sella (mm)	155	155	143	143	143
Lunghezza reggisella (mm)	350	350	400	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
97620-5101	EPIC COMP	Petrolio Satinato Cangiante/Argento	XS
97620-5102			S
97620-5103			M
97620-5104			L
97620-5105			XL
97620-5002	EPIC COMP	Rosso Lucido Perlato/Bianco Metallizzato	S
97620-5003			M
97620-5004			L
97620-5005			XL