

VADO SL 4.0



Nero Satinato / Nero Riflettente

SPECIFICHE TECNICHE

TELAIO	E5 Aluminum, Fitness/Transportation Geometry, bottom bracket motor mount, fully integrated down tube battery, internal cable routing, fender/rack mounts, Smooth Welds, reflective graphics
FORCELLA	Rigid full aluminum disc, Boost™ 12x110mm, front-rack-compatible
ATTACCO	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD-W mount
MANUBRIO	Stout Mini Rise, alloy, 9-degree backsweep, 15mm rise, 31.8mm
MANOPOLE	Specialized Body Geometry Contour, lock-on
FRENO ANT.	Tektro HD-R290, hydraulic disc, 160mm
FRENO POST.	Tektro HD-R290, hydraulic disc, 160mm
CAMBIO POST.	Shimano Deore, Shadow Plus, GS cage, 10-speed
COMANDI	Shimano Deore, RapidFire Plus, 10-speed w/ Optical Gear Display
CASSETTA	Shimano Deore, 10spd, 11-42t
CATENA	KMC e10S, 10-speed w/ Missing Link™
GUARNITURA	Praxis, Forged alloy M30, custom offset
INGRANAGGI	Praxis, 44t, 104BCD
CERCHI	700C disc, 22mm rim depth, 21mm internal width
MOZZO ANT.	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
MOZZO POST.	Specialized alloy rear hub disc, Center Lock™, sealed cartridge bearings, 12x148mm, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Specialized Pathfinder Sport, 700x38c
PNEUMATICO POST.	Specialized Pathfinder Sport, 700x38c
SELLA	Bridge Sport, Steel rails, 155mm
REGGISSELLA	Specialized, alloy, dual-bolt, 25mm offset, 27.2mm
MOTORE	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized SL1-320, fully integrated, 320Wh
CARICATORE	Custom charger, 48V System w/ SL system charger plug
CABLAGGIO	Custom Specialized wiring harness w/ chargeport
SWAT	Specialized Stealth Stem, Light Insert
FANALE ANT.	Lezyne Ebike Hecto STVZO E65, 210Lumens, 12V
FANALINO POST.	Specialized integrated saddle mount, LED Technology, 12V
CAMPANELLO	Simple bell

TURBO VADO SL 4.0	S	M	L	XL
Stack (mm)	595	626	660	696
Reach (mm)	378	401	415	424
Lunghezza Tubo sterzo (mm)	185	217	250	285
Angolo sterzo (degrees)	70	70.5	71	71.5
Altezza movimento centrale (mm)	270	270	270	270
BB Drop (mm)	70	70	70	70
Trail (mm)	71	67	64	61
Lunghezza Forcella (mm)	390	390	390	390
Offset forcella / Rake (mm)	50	50	50	50
Avancorsa (mm)	626	655	675	690
Lunghezza Batticateni (mm)	445	445	445	445
Interasse (mm)	1062	1091	1110	1126
Lunghezza Tubo Orizz. virtuale (mm)	554	587	610	630
Altezza standover (mm)	770	790	815	840
Lunghezza piantone (mm)	415	446.5	494.5	535
Angolo Sella (degrees)	73.5	73.5	73.5	73.5
Lunghezza Pevivella (mm)	170	172.5	172.5	175
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza attacco manubrio (mm)	60	75	75	90
Larghezza sella (mm)	155	155	155	155
Lunghezza reggisella (mm)	350	350	350	350

ART. NR.	DESCRIZIONE	COLORE	MISURA
93920-5102	VADO SL 4.0	Nero Satinato / Nero Riflettente	S
93920-5103			M
93920-5104			L
93920-5105			XL