

S-WORKS TURBO LEVO



Carbonio / Cromo



Rosso / Nero Satinato

S-WORKS TURBO LEVO	S	M	L	XL
Stack (mm)	606	606	634	647
Reach (mm)	415	435	455	480
Lunghezza Tubo sterzo (mm)	95	95	125	140
Angolo sterzo (degrees)	66.04	66.04	66.04	66.04
Altezza Mov. Centr. (mm)	347.5	347.5	347.5	347.5
BB Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Lunghezza intera forcella (mm)	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	729	749	781	812
Lunghezza Batticateni (mm)	455	455	455	455
Interasse (mm)	1182	1202	1235	1266
Lunghezza Tubo Orizz. virtuale (mm)	577	600	631	664
Altezza standover (mm)	760	760	781	787
Lunghezza piantone (mm)	380	410	455	505
Angolo Sella (degrees)	75.04	74.79	74.48	74.14
Lunghezza Pevivella (mm)	165	165	165	165
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	35	35	50	50
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	125	150	170	170

SPECIFICHE TECNICHE

TELAIO	S-Works FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, dropper post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	Fox Float DPS Factory, Kashima, 3- position adjustment, 52.5x210mm, Kashima coating, Rx Trail Tune
FORCELLA	Fox Float 36 Factory, Grip2 damper, 160mm, 51mm rake, HSC, LSC, HSR, LSR, Kabolt axle
ATTACCO	Deity Copperhead, 35.0mm
MANUBRIO	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 35mm
MANOPOLE	Deity, Knuckleduster, Black
FRENO ANT.	Magura MT7 with custom Loic lever blade, 203mm rotor
FRENO POST.	Magura MT7 with custom Loic lever blade, 203mm rotor
CAMBIO POST.	SRAM XX1 Eagle AXS
COMANDI	SRAM AXS Eagle Controller
CASSETTA	Sram XG-1299, 12-speed, 10-52t
CATENA	SRAM XX1
GUARNITURA	Praxis Carbon M30, custom offset
INGRANAGGI	SRAM X-Sync Eagle, 104BCD, 32T, steel
CERCHI	Roval Traverse SL 29, hookless carbon, 30mm inner width, 2Bliss Ready, hand-built, 28h
MOZZO ANT.	Roval Traverse SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing
MOZZO POST.	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing
RAGGI	DT Competition Race
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Bridge, 155/143mm, Hollow Ti-rails
REGGISSELLA	RockShox Reverb AXS, 30.9mm, S: 125, M:150, L/XL: 170mm
MOTORE	Specialized 2.1, custom Rx Trail-tuned motor, 250W nominal
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized M2-700, integrated battery w/rock guard, 700Wh
CARICATORE	Custom charger, 42V4A w/ Rosenberger plug
CABLAGGIO	Custom Specialized harness

ART. NR.	DESCRIZIONE	COLORE	MISURA
95221-0202	LEVO SW CARBON 29 NB	Carbonio / Cromo	S
95221-0203			M
95221-0204			L
95221-0205			XL
95221-0302	LEVO SW CARBON 29 NB	Rosso / Nero Satinato	S
95221-0303			M
95221-0304			L
95221-0305			XL