

TURBO LEVO EXPERT CARBON



Verde Salvia / Verde Foresta

Canna di Fucile / Rosso / Nero

TURBO LEVO EXPERT CARBON	S	M	L	XL
Stack (mm)	606	606	634	647
Reach (mm)	415	435	455	480
Lunghezza Tubo sterzo (mm)	95	95	125	140
Angolo sterzo (degrees)	66.04	66.04	66.04	66.04
Altezza Mov. Centr. (mm)	347.5	347.5	347.5	347.5
BB Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Lunghezza intera forcella (mm)	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	729	749	781	812
Lunghezza Batticateni (mm)	455	455	455	455
Interasse (mm)	1182	1202	1235	1266
Lunghezza Tubo Orizz. virtuale (mm)	577	600	631	664
Altezza standover (mm)	760	760	781	787
Lunghezza piantone (mm)	380	410	455	505
Angolo Sella (degrees)	75.04	74.79	74.48	74.14
Lunghezza Peditivella (mm)	165	165	165	165
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	40	40	50	50
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	361.5	425.5	425.5	470.5

SPECIFICHE TECNICHE

TELAIO	FACT 9m Carbon w/ M5 alloy rear triangle, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, dropper post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	Fox Float DPS Performance Elite, 3- position adjustment, 52.5x210mm, Rx Trail Tune
FORCELLA	Fox Float 36 Performance Elite, Grip2 damper, 160mm, 51mm rake, HSC, LSC, HSR, LSR, Kabolt axle
ATTACCO	Alloy Trail Stem, 35mm bar bore
MANUBRIO	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 780mm, 35mm clamp
MANOPOLE	Deity, Knuckleduster, Black
FRENO ANT.	SRAM Code RS, 4-piston caliper, hydraulic disc, S/M: 200mm, L/XL: 220mm
FRENO POST.	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
CAMBIO POST.	Sram X01 Eagle, 12-speed
COMANDI	SRAM X01 Eagle trigger, 12-speed, single click
CASSETTA	Sram XG-1275, 12-speed, 10-52t
CATENA	SRAM GX Eagle, 12-speed
GUARNITURA	Praxis forged M30, custom offset
INGRANAGGI	SRAM X-Sync Eagle, 104BCD, 32T, steel
CERCHI	Roval Traverse 29 Alloy, 30mm inner width, hand-built, 2Bliss Ready
MOZZO ANT.	Roval, sealed cartridge bearings, 15x110mm spacing, 28h
MOZZO POST.	Roval DT Swiss 360, 3-pawl design, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Competition Race
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Bridge Comp, Hollow Cr-mo rails, 155/143mm
REGGISELLA	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S: 125mm, M/L: 150mm, XL: 170mm
MOTORE	Specialized 2.1, custom Rx Trail-tuned motor, 250W nominal
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized M2-700, integrated battery w/rock guard, 700Wh
CARICATORE	Custom charger, 42V4A w/ Rosenberger plug
CABLAGGIO	Custom Specialized harness

ART. NR.	DESCRIZIONE	COLORE	MISURA
95221-3202	LEVO EXPERT CARBON 29 NB	Canna di Fucile / Rosso / Nero	S
95221-3203			M
95221-3204			L
95221-3205			XL
95221-3502	LEVO EXPERT CARBON 29 NB	Verde Salvia / Verde Foresta	S
95221-3503			M
95221-3504			L
95221-3505			XL