



Bianco Metallizzato / Argento / Nero



Nero / Perlato Blu / Grigio Tortora / Nero

<https://www.bi-bike.it/wp-content/uploads/2020/09/95020-72.pdf>

SPECIFICHE TECNICHE

TELAIO	E5 Aluminum, low-entry frame, bottom bracket motor mount, Ground Control Geometry, fully integrated & lockable down tube battery, internal cable routing, fender/rack mounts, Smooth Welds, 141mm QR Dropout
FORCELLA	SR Suntour MOBIE30, steel steerer, 9mm open dropout, 50mm of travel
ATTACCO	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
MANUBRIO	Specialized, alloy, 30-degree backsweep, 26mm rise, 680mm width, 31.8mm
MANOPOLE	Body Geometry Women's Contour
FRENO ANT.	Shimano BR-MT200, hydraulic disc, 180mm
FRENO POST.	Shimano BR-MT200, hydraulic disc, 160mm
CAMBIO POST.	Shimano Alivio, Shadow Design, SGS cage, 9-speed
COMANDI	Shimano Alivio, 9-speed w/ Optical Gear Display
CASSETTA	Shimano CS-HG200, 9-speed, 11-36t
CATENA	KMC e9T.NPNP, e-bike chain, 9-speed w/ Missing Link™
GUARNITURA	Custom alloy forged crankarms
INGRANAGGI	40T, custom alloy
CERCHI	700C disc, double-wall alloy, pinned, no eyelets
MOZZO ANT.	Specialized front hub disc, sealed bearings, 15x100mm thru-axle, 32h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 32h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Nimbus II Armadillo Reflect, 60 TPI, 700c x 50c
PNEUMATICO POST.	Nimbus II Armadillo Reflect, 60 TPI, 700c x 50c
SELLA	Body Geometry Comfort Gel, 200mm w/ SWAT™ Mount
REGGISELLA	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm
MOTORE	Specialized 1.2 E, custom Rx Street-tuned motor, 250W nominal
UI/REMOTE	Specialized TCD-W w/ handlebar remote & built-in anti-theft feature, Bluetooth® connectivity, 5 available display pages
BATTERIA	Specialized U1-460, On/Off button, state of charge display, 460Wh
CARICATORE	Custom Specialized 42V2A Charger w/ Rosenberger plug, AC power cord included
CABLAGGIO	Custom Specialized harness
FANALE ANT.	Herrmans MR4 e-Bike, stainless bracket for suspension fork, 6V
FANALINO POST.	Herrmans H-Trace Mini e-Bike, 220-degree visibility, fender-mount
CAVALETTO	Specialized kickstand, 40mm mount
PARAFANGHI	Specialized DRYTECH fenders, 52mm width, stainless steel fenderstays
CAMPANELLO	Simple bell

TURBO COMO 3.0 700C LOW-ENTRY

	S	L
Stack (mm)	685	713
Reach (mm)	329	357
Lunghezza piantone c/f (mm)	380	480
Lunghezza Tubo Orizz. virtuale (mm)	620	660
Lunghezza Batticateni (mm)	485	485
Interasse (mm)	1102	1142
Altezza standover (mm)	534	526
Lunghezza Tubo sterzo (mm)	210	240
BB Drop (mm)	75	75
Angolo sterzo (degrees)	68	68
Angolo Sella reale (degrees)	68	68
Lunghezza Pedivella (mm)	170	170
Larghezza Manubrio (mm)	680	680
Lunghezza attacco manubrio (mm)	60	60
Larghezza sella (mm)	200	200
Lunghezza reggisella (mm)	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
90420-7602	COMO 3.0 LOW ENTRY 700C NB	Bianco Metallizzato / Argento / Nero	S
90420-7604			L
90420-7402	COMO 3.0 LOW ENTRY 700C NB	Nero / Perlato Blu / Grigio Tortora / Nero	S
90420-7404			L