

IMAGE COMING SOON

Grigio Fumo Lucido / Grigio / Nero Satinato Riflettente

SPECIFICHE TECNICHE	
TELAIO	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully manipulated butted tubing, internal cable routing, flat-mount disc, 12x142mm thru-axle, Plug + Play rack/fender mounts
FORCELLA	Carbon monocoque, 12x100mm flat thru-axle, flat mount disc, Future Shock-compatible steerer
MANUBRIO	Stout Mini Rise, alloy, 9-degree backsweep, 15mm rise, 31.8mm
ATTACCO	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
NASTRO	Specialized Neutralizer, Body Geometry, locking grip
SELLA	Bridge Comp, Hollow Cr-mo rails, 155/143mm
REGGISELLA	Alloy, 2-bolt, 14mm offset, 27.2mm
FRENO ANT.	Shimano BR-MT200, hydraulic disc, 160mm
FRENO POST.	Shimano BR-MT200, hydraulic disc, 160mm
COMANDI	Shimano Deore, 5100 11-speed
CAMBIO POST.	Shimano Deore, 5100 11-speed
CASSETTA	Shimano Deore, 5100 11-speed - 11-42t
INGRANAGGI	Aluminum 40T, Narrow-wide
MOVIM. CENTR.	Threaded BSA 68mm
CATENA	KMC X10, 10-speed w/ reusable Missing Link™
CERCHI	700C disc, double-wall alloy, 22mm depth, 21mm internal width, 32h
MOZZO ANT.	Alloy, Center Lock™ disc, high-low flange, sealed cartridge bearings, 12x100mm spacing, 24h
MOZZO POST.	Alloy, Center Lock™ disc, high-low flange, sealed cartridge bearings, 12x142mm spacing, 28h
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Pathfinder Sport, 700x38mm
PNEUMATICO POST.	Pathfinder Sport, 700x38mm

SIRRUS X 4.0	XS	S	M	L	XL
Stack (mm)	590	606	635	651	672
Reach (mm)	371	376	382	386	398
Lunghezza Tubo sterzo (mm)	125	143	169	186	208
Angolo sterzo (degrees)	70	70	71	71	71
Altezza movimento centrale (mm)	284	284	284	284	284
BB Drop (mm)	70	70	70	70	70
Trail (mm)	75	75	68	68	68
Lunghezza Forcella (mm)	395	395	395	395	395
Offset forcella / Rake (mm)	51	51	51	51	51
Avancorsa (mm)	618	629	634	644	663
Lunghezza Batticateni (mm)	440	440	440	440	440
Interasse (mm)	1049	1060	1065	1074	1093
Lunghezza Tubo Orizz. virtuale (mm)	549	559	572	581	599
Altezza standover (mm)	722	750	778	810	831
Lunghezza piantone (mm)	395	440	470	510	530
Angolo Sella (degrees)	73.5	73.5	73.5	73.5	73.5
Lunghezza Pedivella (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	660	660	680	680	680
Lunghezza attacco manubrio (mm)	60	70	80	90	100
Larghezza sella (mm)	155	155	143	143	143
Lunghezza reggisella (mm)	300	350	350	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
92421-5001	SIRRUS X 4.0	Grigio Fumo Lucido / Grigio / Nero Satinato Riflettente	XS
92421-5002			S
92421-5003			M
92421-5004			L
92421-5005			XL