



Blu / Nero / Argento



Nero con Kit Decalco

SPECIFICHE TECNICHE

TELAIO	E5 Aluminum, bottom bracket motor mount, Fitness/Transportation Geometry, fully integrated & lockable down tube battery, internal cable routing, fender/rack mounts, Smooth Welds
FORCELLA	SR SunTour MOBIE30, custom crown, steel steerer, 9mm open dropout, 50mm of travel
ATTACCO	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
MANUBRIO	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
MANOPOLE	Specialized Body Geometry Contour, lock-on
FRENO ANT.	Tektro HD-T275, hydraulic disc, 180mm
FRENO POST.	Tektro HD-T275, hydraulic disc, 160mm
CAMBIO POST.	Shimano Alivio, Shadow Design, SGS cage, 9-speed
COMANDI	Shimano Alivio, 9-speed w/ Optical Gear Display
CASSETTA	Shimano CS-HG200, 9-speed, 11-36t
CATENA	KMC e9T.NPNP, e-bike chain, 9-speed w/ Missing Link™
GUARNITURA	Custom alloy forged crankarms
INGRANAGGI	40T, custom alloy
CERCHI	700c disc, double-wall alloy, pinned, no eyelets
MOZZO ANT.	Specialized 6-bolt disc, ball bearings, 9x100mm spacing, 32h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 32h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Trigger Sport Reflect, 700x47c
PNEUMATICO POST.	Trigger Sport Reflect, 700x47c
SELLA	Bridge Sport, Steel rails, 155mm
REGGISELLA	Specialized 2-bolt head, forged alloy, 8mm offset, micro-adjust, 30.9mm
MOTORE	Specialized 1.2 E, custom Rx Street-tuned motor, 250W nominal
UI/REMOTE	Specialized TCD-W w/ handlebar remote & built-in anti-theft feature, Bluetooth® connectivity, 5 available display pages
BATTERIA	Specialized U1-460, On/Off button, state of charge display, 460Wh
CARICATORE	Custom Specialized 42V2A Charger w/ Rosenberger plug, AC power cord included
CABLAGGIO	Custom Specialized harness
FANALE ANT.	Herrmans MR4 e-Bike, stainless bracket for suspension fork, 6V
FANALINO POST.	Herrmans H-Trace Mini e-Bike, 220-degree visibility, fender-mount
CAVALETTO	Specialized kickstand, 40mm mount
PARAFANGHI	DRYTECH fenders, 52mm width, stainless steel fenderstays
CAMPANELLO	Simple bell

TURBO VADO 3.0	S	M	L	XL
Stack (mm)	619	619	629	652
Reach (mm)	396	406	428	441
Lunghezza piantone c/f (mm)	400	450	500	550
BB Drop (mm)	-70	-70	-70	-70
Lunghezza Batticateni (mm)	478	478	478	478
Angolo sterzo (degrees)	70	70	70	70
Offset forcella / Rake (mm)	44	44	44	44
Trail (mm)	86	86	86	86
Avancorsa (mm)	647	657	682	704
Interasse (mm)	1116	1126	1152	1173
Altezza standover (mm)	762	800	833	875
Lunghezza Tubo sterzo (mm)	135	135	145	170
Lunghezza Peditivella (mm)	170	170	175	175
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza attacco manubrio (mm)	60	75	75	90
Larghezza sella (mm)	155	155	155	155
Lunghezza reggisella (mm)	300	350	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
95020-7202	VADO 3.0 NB	Blu / Nero / Argento	S
95020-7203			M
95020-7204			L
95020-7205			XL
95020-7902	TURBO VADO 3.0 UOMO	Antracite / Nero / Argento	S
95020-7903			M
95020-7904			L
95020-7905			XL