

IMAGE COMING SOON

Verde Foresta / Nero / Argento

SPECIFICHE TECNICHE

TELAIO	E5 Aluminum, bottom bracket motor mount, Fitness/Transportation Geometry, fully integrated & lockable down tube battery, internal cable routing, fender/rack mounts, Smooth Welds
FORCELLA	SR Suntour NCX E25, steel steerer, 15mm thru-axle, 44mm offset, 50mm of travel
ATTACCO	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
MANUBRIO	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
MANOPOLE	Body Geometry Women's Contour
FRENO ANT.	Shimano BR-MT200, hydraulic disc, 180mm
FRENO POST.	Shimano BR-MT200, hydraulic disc, 160mm
CAMBIO POST.	Shimano Deore, Shadow Plus, GS cage, 10-speed
COMANDI	Shimano Deore, RapidFire Plus, 10-speed w/ Optical Gear Display
CASSETTA	Shimano Deore, 10spd, 11-42t
CATENA	KMC X10eT, 10-speed w/ Missing Link™
GUARNITURA	Custom alloy forged crankarms
INGRANAGGI	40T, custom alloy
CERCHI	700c disc, double-wall alloy, pinned, 32h
MOZZO ANT.	Specialized front hub disc, sealed bearings, 15x100mm thru-axle, 32h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 32h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Trigger Sport Reflect, 700x47c
PNEUMATICO POST.	Trigger Sport Reflect, 700x47c
SELLA	Bridge Sport, Steel rails, 155mm
REGGISELLA	Specialized 2-bolt head, forged alloy, 8mm offset, micro-adjust, 30.9mm
MOTORE	Specialized 1.2, custom Rx Street-tuned motor, 250W nominal
UI/REMOTE	Specialized TCD-W w/ handlebar remote & built-in anti-theft feature, Bluetooth® connectivity, 5 available display pages
BATTERIA	Specialized U1-500, On/Off button, state of charge display, 500Wh
CARICATORE	Custom charger, 42V4A w/ Rosenberger plug
CABLAGGIO	Custom Specialized harness
FANALE ANT.	Herrmans H-Black MR8 e-Bike, stainless bracket for suspension fork
FANALINO POST.	Herrmans H-Trace Mini e-Bike, 220-degree visibility, fender-mount
CAVALETTO	Specialized kickstand, 40mm mount
PARAFANGHI	DRYTECH fenders, 52mm width, stainless steel fenderstays
CAMPANELLO	Simple bell

TURBO VADO 4.0 STEP-THROUGH

	S	M	L	XL
Stack (mm)	619	629	629	652
Reach (mm)	396	404	428	441
Lunghezza piantone c/f (mm)	400	450	485	535
BB Drop (mm)	-70	-70	-70	-70
Lunghezza Batticatena (mm)	478	478	478	478
Angolo sterzo (degrees)	70	70	70	70
Offset forcella / Rake (mm)	44	44	44	44
Trail (mm)	86	86	86	86
Avancorsa (mm)	647	658	683	704
Interasse (mm)	1116	1127	1152	1173
Altezza standover (mm)	715	720	727	744
Lunghezza Tubo sterzo (mm)	145	145	155	170
Lunghezza Pedivella (mm)	170	170	175	175
Larghezza Manubrio (mm)	680	680	680	680
Lunghezza attacco manubrio (mm)	60	75	75	90
Larghezza sella (mm)	155	155	155	155
Lunghezza reggisella (mm)	300	350	400	400

ART. NR.	DESCRIZIONE	COLORE	MISURA
95021-5702	VADO 4.0 STEP THROUGH NB	Verde Foresta / Nero /Argento	S
95021-5703			M
95021-5704			L
95021-5705			XL