

TURBO LEVO M5



Argilla / Nero / Argento



Giallo Ottone



Nero / Nero Lucido / Grigio Fumo

TURBO LEVO M5	S	M	L	XL
Stack (mm)	606	606	634	647
Reach (mm)	415	435	455	480
Lunghezza Tubo sterzo (mm)	95	95	125	140
Angolo sterzo (degrees)	66.04	66.04	66.04	66.04
Altezza Mov. Centr. (mm)	347.5	347.5	347.5	347.5
BB Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Lunghezza intera forcella (mm)	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	729	749	781	812
Lunghezza Batticateni (mm)	455	455	455	455
Interasse (mm)	1182	1202	1235	1266
Lunghezza Tubo Orizz. virtuale (mm)	577	600	631	664
Altezza standover (mm)	760	760	781	787
Lunghezza piantone (mm)	380	410	455	505
Angolo Sella (degrees)	75.04	74.79	74.48	74.14
Lunghezza Pedivella (mm)	165	165	165	165
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	40	40	50	50
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	406	456	456	496

SPECIFICHE TECNICHE	
TELAIO	Specialized M5 Premium Aluminum, 29 Trail Geometry, integrated down tube battery, enclosed internal cable, dropper post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	RockShox Deluxe Select w/ custom air valve, 52.5x210mm
FORCELLA	Rockshox 35 Silver TK, 160mm travel TurnKey damper
ATTACCO	Alloy Trail Stem, 35mm bar bore
MANUBRIO	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 800mm width
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Guide RE, metallic pads
FRENO POST.	SRAM Guide RE, 4-piston caliper, hydraulic disc, 200mm
CAMBIO POST.	SRAM NX Eagle, 12-speed
COMANDI	SRAM NX Eagle, single-click lever
CASSETTA	SRAM NX Eagle, 12-speed, 11-50t
CATENA	SRAM NX Eagle, 12-speed
GUARNITURA	Praxis forged M30, custom offset
INGRANAGGI	SRAM X-Sync Eagle, 104BCD, 32T, steel
CERCHI	Roval 29, hookless alloy, 30mm inner width, tubeless ready
MOZZO ANT.	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
MOZZO POST.	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Body Geometry Bridge Saddle, steel rails
REGGISELLA	TranzX dropper, 34.9mm, XS-S: 100mm, M: 120mm, L/XL: 150mm Travel
MOTORE	Specialized 2.1, custom Rx Trail-tuned motor, 250W nominal
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized M2-500, integrated battery w/rock guard, 500Wh
CARICATORE	Custom charger, 42V4A w/ Rosenberger plug
CABLAGGIO	Custom Specialized harness

ART. NR.	DESCRIZIONE	COLORE	MISURA
95221-7502	LEVO 29 NB	Argilla / Nero / Argento	S
95221-7503			M
95221-7504			L
95221-7302	LEVO 29 NB	Giallo Ottone	S
95221-7303			M
95221-7304			L
95221-7305			XL
95221-7202	LEVO 29 NB	Nero / Nero Lucido / Grigio Fumo	S
95221-7203			M
95221-7204			L
95221-7205			XL