

# TURBO LEVO SL COMP



Rosso Rocket / Nero



Turchese / Nero

## SPECIFICHE TECNICHE

TELAIO	Specialized M5 Premium Aluminum, 29 Trail Geometry, integrated down tube battery, enclosed internal cable, dropper post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	FOX Float DPS Performance, 3-position adjustment, 52.5x210mm, Rx Trail Tune
FORCELLA	Fox Float 34 Rhythm, Grip damper, 150mm, Sweep-Adj, 51mm rake, Kabolt Axle
ATTACCO	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, XS 720mm, S-XL 750mm,
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Guide RE, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	SRAM Guide RE, metallic pads, 180mm
CAMBIO POST.	SRAM NX Eagle, 12-speed
COMANDI	SRAM NX Eagle, trigger, 12-speed
CASSETTA	SRAM NX Eagle, 12-speed, 11-50t
CATENA	SRAM NX Eagle, 12-speed
GUARNITURA	Praxis, forged M30, custom offset
INGRANAGGI	SRAM X-Sync Eagle, 94 BCD, 30T
CERCHI	Roval 29, hookless alloy, 30mm inner width, tubeless ready
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 32h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Bridge Comp, Hollow Cr-mo rails, 155/143mm
REGGISELLA	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S: 125mm, M/L: 150mm, XL: 170mm
MOTORE	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized SL1-320, fully integrated, 320Wh
CARICATORE	Custom charger, 48V System w/ SL system charger plug
CABLAGGIO	Custom Specialized wiring harness w/ chargeport

TURBO LEVO SL COMP	XS	S	M	L	XL
Stack (mm)	579	606	606	633	647
Reach (mm)	395	415	435	455	481
Lunghezza Tubo sterzo (mm)	95	95	95	125	140
Angolo sterzo (degrees)	66	66	66	66	66
Altezza Mov. Centr. (mm)	347	347	347	347	347
BB Drop (mm)	27	27	27	27	27
Trail (mm)	110	110	110	110	100
Lunghezza intera forcella (mm)	560	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51	51
Avancorsa (mm)	709	729	749	781	813
Lunghezza Batticateni (mm)	437	437	437	437	437
Interasse (mm)	1145	1165	1185	1217	1249
Lunghezza Tubo Orizz. virtuale (mm)	551	573	595	628	664
Altezza standover (mm)	767	771	774	789	789
Lunghezza piantone (mm)	380	390	410	455	505
Angolo Sella (degrees)	75.6	75.4	75.2	74.7	74.2
Lunghezza Pedivella (mm)	165	165	165	170	170
Larghezza Manubrio (mm)	750	780	780	780	780
Lunghezza attacco manubrio (mm)	45	45	45	45	45
Larghezza sella (mm)	143	155	143	143	143
Lunghezza reggisella (mm)	315.5	361.5	425.5	425.5	470.5

ART. NR.	DESCRIZIONE	COLORE	MISURA
96820-5101	LEVO SL COMP	Rosso Rocket / Nero	XS
96820-5102			S
96820-5103			M
96820-5104			L
96820-5105			XL
96820-5001	LEVO SL COMP	Turchese / Nero	XS
96820-5002			S
96820-5003			M
96820-5004			L
96820-5005			XL