



Carbonio / Bronzo / Carbonio Lucido

SPECIFICHE TECNICHE

TELAIO	FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, dropper post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	Fox Float DPX2 Factory, 3- position adjustment, 52.5x210mm, Rx Trail Tune
FORCELLA	Fox Float 36 Factory, Grip2 damper, 150mm, 51mm rake, HSC, LSC, HSR, LSR, Kabolt axle
ATTACCO	Deity Copperhead, 35.0mm
MANUBRIO	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 35mm
MANOPOLE	Deity, Knuckleduster, Black
FRENO ANT.	Magura MT7 with custom Loic lever blade, 203mm rotor
FRENO POST.	Magura MT7 with custom Loic lever blade, 180mm rotor S/M, 203mm rotor L/XL
CAMBIO POST.	SRAM XX1 Eagle AXS
COMANDI	SRAM AXS Eagle Controller
CASSETTA	Sram XG-1299, 12-speed, 10-52t
CATENA	SRAM XX1 Eagle
GUARNITURA	Praxis, carbon M30, custom offset
INGRANAGGI	SRAM X-Sync Eagle, 94 BCD, 30T
CERCHI	Roval Traverse SL 29, hookless carbon, 30mm inner width, 2Bliss Ready, hand-built, 28h
MOZZO ANT.	Roval Traverse SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing
MOZZO POST.	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing
RAGGI	DT Competition Race
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Bridge, 155/143mm, Hollow Ti-rails
REGGISSELLA	RockShox Reverb AXS, 30.9mm, S: 125, M:150, L/XL: 170mm
MOTORE	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized SL1-320, fully integrated, 320Wh
CARICATORE	Custom charger, 48V System w/ SL system charger plug
CABLAGGIO	Custom Specialized wiring harness w/ chargeport

S-WORKS TURBO LEVO SL	S	M	L	XL
Stack (mm)	606	606	633	647
Reach (mm)	415	435	455	480
Lunghezza Tubo sterzo (mm)	95	95	125	140
Angolo sterzo (degrees)	66	66	66	66
Altezza movimento centrale (mm)	348	348	348	348
BB Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Lunghezza Forcella (mm)	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	729	749	781	812
Lunghezza Batticateni (mm)	437	437	437	437
Interasse (mm)	1165	1185	1217	1248
Lunghezza Tubo Orizz. virtuale (mm)	574	597	629	663
Altezza standover (mm)	787	790	807	814
Lunghezza piantone (mm)	390	410	455	505
Angolo Sella (degrees)	75.3	75	74.6	74.2
Lunghezza Pedivella (mm)	165	165	170	170
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	35	35	50	50
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	125	150	170	170

ART. NR.	DESCRIZIONE	COLORE	MISURA
96821-0002	LEVO SL SW CARBON	Carbonio / Bronzo / Carbonio Lucido	S
96821-0003			M
96821-0004			L
96821-0005			XL