

# TURBO LEVO SL EXPERT CARBON



Grigio Corazzata / Nero



Salvia Lucido / Verde Foresta

## SPECIFICHE TECNICHE

TELAIO	FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, dropper post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	Fox Float DPX2 Performance Elite, 3- position adjustment, 52.5x210mm, Rx Trail Tune
FORCELLA	Fox Float 36, Performance Elite, Grip2 damper, 150mm, 51mm rake, HSC, LSC, HSR, LSR, Kabolt axle
ATTACCO	Alloy Trail Stem, 35mm bar bore
MANUBRIO	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 780mm, 35mm clamp
MANOPOLE	Deity, Knuckleduster, Black
FRENO ANT.	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm
CAMBIO POST.	Sram X01 Eagle, 12-speed
COMANDI	SRAM X01, trigger, 12-speed
CASSETTA	Sram XG-1275, 12-speed, 10-52t
CATENA	SRAM GX Eagle, 12-speed
GUARNITURA	Praxis, forged M30, custom offset
INGRANAGGI	SRAM X-Sync Eagle, 94 BCD, 30T
CERCHI	Roval Traverse 29 Alloy, 30mm inner width, hand-built, 2Bliss Ready
MOZZO ANT.	Roval, sealed cartridge bearings, 15x110mm spacing, 28h
MOZZO POST.	Roval DT Swiss 360, 3-pawl design, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Competition Race
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Bridge Comp, Hollow Cr-mo rails, 155/143mm
REGGISELLA	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S: 125mm, M/L: 150mm, XL: 170mm
MOTORE	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized SL1-320, fully integrated, 320Wh
CARICATORE	Custom charger, 48V System w/ SL system charger plug
CABLAGGIO	Custom Specialized wiring harness w/ chargeport

## TURBO LEVO SL EXPERT CARBON

	S	M	L	XL
Stack (mm)	606	606	633	647
Reach (mm)	415	435	455	480
Lunghezza Tubo sterzo (mm)	95	95	125	140
Angolo sterzo (degrees)	66	66	66	66
Altezza movimento centrale (mm)	348	348	348	348
BB Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Lunghezza Forcella (mm)	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	729	749	781	812
Lunghezza Batticateni (mm)	437	437	437	437
Interasse (mm)	1165	1185	1217	1248
Lunghezza Tubo Orizz. virtuale (mm)	574	597	629	663
Altezza standover (mm)	787	790	807	814
Lunghezza piantone (mm)	390	410	455	505
Angolo Sella (degrees)	75.3	75	74.6	74.2
Lunghezza Pedivella (mm)	165	165	170	170
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	40	40	50	50
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	361.5	425.5	425.5	470.5

ART. NR.	DESCRIZIONE	COLORE	MISURA
96821-3002	LEVO SL EXPERT CARBON	Grigio Corazzata / Nero	S
96821-3003			M
96821-3004			L
96821-3005			XL
96821-3202	LEVO SL EXPERT CARBON	Salvia Lucido / Verde Foresta	S
96821-3203			M
96821-3204			L
96821-3205			XL