

# TURBO LEVO SL COMP CARBON



Verde / Nero



Mirtillo / Nero



Nero / Canna di Fucile



Rosso / Nero

## SPECIFICHE TECNICHE

TELAIO	FACT 11m full carbon, 29 Trail Geometry, Integrated down tube battery, enclosed internal cable, dropper post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
AMMORTIZZATORE	FOX Float DPS Performance, 3-position adjustment, 52.5x210mm, Rx Trail Tune
FORCELLA	Fox Float 34 Rhythm, Grip damper, 150mm, Sweep-Adj, 51mm rake, Kabolt Axle
ATTACCO	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise
MANUBRIO	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 31.8mm clamp, XS 720mm, S-XL 750mm,
MANOPOLE	Specialized Trail Grips
FRENO ANT.	SRAM Guide RE, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	SRAM Guide RE, metallic pads, 180mm
CAMBIO POST.	SRAM NX Eagle, 12-speed
COMANDI	SRAM NX Eagle, trigger, 12-speed
CASSETTA	SRAM NX Eagle, 12-speed, 11-50t
CATENA	SRAM NX Eagle, 12-speed
GUARNITURA	Praxis, forged M30, custom offset
INGRANAGGI	SRAM X-Sync Eagle, 94 BCD, 30T
CERCHI	Roval 29, hookless alloy, 30mm inner width, tubeless ready
MOZZO ANT.	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
MOZZO POST.	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 32h
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 2Bliss Ready, 29x2.3"
SELLA	Bridge Comp, Hollow Cr-mo rails, 155/143mm
REGGISELLA	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SRL LE lever, 34.9mm, S: 125mm, M/L: 150mm, XL: 170mm
MOTORE	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERIA	Specialized SL1-320, fully integrated, 320Wh
CARICATORE	Custom charger, 48V System w/ SL system charger plug
CABLAGGIO	Custom Specialized wiring harness w/ chargeport

ART. NR.	DESCRIZIONE	COLORE	MISURA
96821-5302	LEVO SL COMP CARBON	Verde / Nero	S
96821-5303			M
96821-5304			L
96821-5305			XL
96820-5202	LEVO SL COMP CARBON	Mirtillo / Nero	S
96820-5203			M
96820-5204			L
96820-5402	LEVO SL COMP CARBON	Nero / Canna di Fucile	S
96820-5403			M
96820-5404			L
96820-5405			XL
96821-5502	LEVO SL COMP CARBON	Rosso / Nero	S
96821-5503			M
96821-5504			L
96821-5505		Rosso / Nero	XL

## TURBO LEVO SL COMP CARBON

	S	M	L	XL
Stack (mm)	606	606	633	647
Reach (mm)	415	435	455	480
Lunghezza Tubo sterzo (mm)	95	95	125	140
Angolo sterzo (degrees)	66	66	66	66
Altezza movimento centrale (mm)	348	348	348	348
BB Drop (mm)	27	27	27	27
Trail (mm)	111	111	111	111
Lunghezza Forcella (mm)	560	560	560	560
Offset forcella / Rake (mm)	51	51	51	51
Avancorsa (mm)	729	749	781	812
Lunghezza Batticateni (mm)	437	437	437	437
Interasse (mm)	1165	1185	1217	1248
Lunghezza Tubo Orizz. virtuale (mm)	574	597	629	663
Altezza standover (mm)	787	790	807	814
Lunghezza piantone (mm)	390	410	455	505
Angolo Sella (degrees)	75.3	75	74.6	74.2
Lunghezza Peditivella (°)	165	165	170	170
Larghezza Manubrio (mm)	780	780	780	780
Lunghezza attacco manubrio (°)	45	45	45	45
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (°)	361.5	425.5	425.5	470.5