

S-WORKS STUMPJUMPER



SATIN REDWOOD / SMOKE / CARBON

S-WORKS STUMPJUMPER	S1	S2	S3	S4	S5	S6
Stack (BB basso) (mm)	614	613	622	632	641	650
Stack (BB alto) (mm)	610	609	618	627	636	646
Reach (BB basso) (mm)	410	430	450	475	500	530
Reach (BB alto) (mm)	415	435	455	480	505	535
Lunghezza Tubo sterzo (mm)	95	100	110	120	130	140
Angolo Sterzo (BB basso) (°)	65	65	65	65	65	65
Angolo Sterzo (BB alto) (°)	65.5	65.5	65.5	65.5	65.5	65.5
Altezza BB (Basso) (mm)	328	333	333	333	333	333
Altezza BB (Alto) (mm)	335	340	340	340	340	340
BB Drop (basso) (mm)	47	42	42	42	42	42
BB Drop (alto) (mm)	40	35	35	35	35	35
Trail (BB basso) (mm)	126	126	126	126	126	126
Trail (BB alto) (mm)	123	123	123	123	123	123
Lunghezza Forcella (intera) (mm)	550	550	550	550	550	550
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	724	746	770	800	829	863
Chainstay Length (mm)	432	432	432	432	442	442
Wheelbase (mm)	1152	1175	1200	1228	1268	1302
Top-tube Length (horizontal) (mm)	563	583	605	632	660	692
Bike Standover Height (mm)	730	734	744	749	757	757
Seat Tube Length (mm)	385	385	405	425	445	465
Angolo Sella (BB basso) (°)	76	76	76	76	76	76
Angolo Sella (BB alto) (°)	76.5	76.5	76.5	76.5	76.5	76.5
Massimo Inserim.Reggisella (mm)	220	220	240	260	280	300
Minimo Inserim.Reggisella (mm)	80	80	80	80	80	80

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	FACT 11m carbon chassis and rear-end, asymmetrical design, 29 Trail Geometry, SWAT™ Door integration, flip chip Head Tube/Bottom Bracket adjustment, threaded BB, fully enclosed internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
SWAT	SWAT™ Door integration
AMMORTIZZATORE	FOX FLOAT DPS Factory, Rx Trail Tune, EVOL Air sleeve, Kashima Coat, 3-position adjustment w/ Open Mode Adjustment, 190x45mm
FORCELLA	FOX FLOAT 34 Factory, GRIP2 damper, Kashima Coating, 15x110mm, 44mm offset, 140mm of travel
ATTACCO	Deity Copperhead, 35.0mm
MANUBRIO	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 35mm
MANOPOLE	Deity, Knuckleduster, Black
FRENO ANT.	SRAM G2 ULTIMATE, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	SRAM G2 ULTIMATE, 4-piston caliper, hydraulic disc, 180mm
CAMBIO POST.	SRAM XX1 Eagle AXS
COMANDI	SRAM XX1 Eagle AXS
CATENA	SRAM XX1, 12 speed
GUARNITURA	SRAM XX1 Eagle, DUB, S1:165mm, S2-S5: 170mm, S6: 175mm
INGRANAGGI	Steel, 30T
CERCHI	Roval Control 240, hookless carbon, 29mm inner width, hand-built, 2Bliss Ready
MOZZO ANT.	DT Swiss 240, sealed cartridge bearings, 15x110mm spacing, 28h
MOZZO POST.	DT Swiss 240, Ratchet EXP, 36t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
RAGGI	DT Swiss Competition Race
PNEUMATICO ANT.	Butcher, GRID casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Purgatory, GRID Casing, GRIPTON® compound, 29x2.3"
SELLA	Bridge, 155/143mm, Hollow Ti-rails
REGGISELLA	RockShox Reverb AXS, 30.9, 1X remote, (S1:100mm, S2: 125mm, S3: 150mm, S4-S6: 170mm)

ART. NR.	DESCRIZIONE	COLORE	MISURA
93321-0002	SJ SW	SATIN REDWOOD / SMOKE S2 / CARBON	
93321-0003			S3
93321-0004			S4
93321-0005			S5