

STUMPJUMPER COMP CARBON



GLOSS WHITE MOUNTAINS / BLACK

STUMPJUMPER COMP CARBON

	S1	S2	S3	S4	S5	S6
Stack (BB basso) (mm)	614	613	622	632	641	650
Stack (BB alto) (mm)	610	609	618	627	636	646
Reach (BB basso) (mm)	410	430	450	475	500	530
Reach (BB alto) (mm)	415	435	455	480	505	535
Lunghezza Tubo sterzo (mm)	95	100	110	120	130	140
Angolo Sterzo (BB basso) (°)	65	65	65	65	65	65
Angolo Sterzo (BB alto) (°)	65.5	65.5	65.5	65.5	65.5	65.5
Altezza BB (Basso) (mm)	328	333	333	333	333	333
Altezza BB (Alto) (mm)	335	340	340	340	340	340
BB Drop (basso) (mm)	47	42	42	42	42	42
BB Drop (alto) (mm)	40	35	35	35	35	35
Trail (BB basso) (mm)	126	126	126	126	126	126
Trail (BB alto) (mm)	123	123	123	123	123	123
Lunghezza Forcella (intera) (mm)	550	550	550	550	550	550
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	724	746	770	800	829	863
Chainstay Length (mm)	432	432	432	432	442	442
Wheelbase (mm)	1152	1175	1200	1228	1268	1302
Top-tube Length (horizontal) (mm)	563	583	605	632	660	692
Bike Standover Height (mm)	730	734	744	749	757	757
Seat Tube Length (mm)	385	385	405	425	445	465
Angolo Sella (BB basso) (°)	76	76	76	76	76	76
Angolo Sella (BB alto) (°)	76.5	76.5	76.5	76.5	76.5	76.5
Massimo Inserim.Reggisella (mm)	220	220	240	260	280	300
Minimo Inserim.Reggisella (mm)	80	80	80	80	80	80
Lunghezza Pedivella (mm)	165	170	170	170	170	175
Lunghezza Manubrio (mm)	780	780	780	780	780	780
Lunghezza attacco manubrio (mm)	40	40	50	50	50	50
Larghezza sella (mm)	155	155	143	143	143	143

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	FACT 11m carbon chassis and rear-end, asymmetrical design, 29 Trail Geometry, SWAT™ Door integration, flip chip Head Tube/Bottom Bracket adjustment, threaded BB, fully enclosed internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
SWAT	SWAT™ Door integration
AMMORTIZZATORE	FOX FLOAT DPS Performance, Rx Trail Tune, rebound and 3-position compression adjust, 190x45mm
FORCELLA	FOX FLOAT 34 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset,140mm of travel
ATTACCO	Alloy Trail Stem, 35mm bar bore
MANUBRIO	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 800mm width
FRENO ANT.	Shimano SLX M7120, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	Shimano SLX M7120, 4-piston caliper, hydraulic disc, 180mm
CAMBIO POST.	Shimano SLX M7100, SGS, 12-speed
COMANDI	Shimano SLX, M7100, 12spd
CATENA	Shimano SLX, M7100, 12-speed
GUARNITURA	Shimano SLX, S1:165mm, S2-S5: 170mm, S6: 175mm
INGRANAGGI	30T
CERCHI	Roval 29, hookless alloy, 30mm inner width, tubeless ready
MOZZO ANT.	Shimano MT400-B, Centerlock 28h, 15x110 Boost
MOZZO POST.	Shimano MT510-B, Centerlock 28h, 12x148 Boost, Microspline
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Butcher, GRID casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Purgatory, GRID Casing, GRIPTON® compound, 29x2.3"
SELLA	Bridge Comp, Hollow Cr-mo rails, 155/143mm
REGGISELLA	X-Fusion Manic, infinite adjustable, remote SRL LE lever, 34.9 (S1:100mm, S2: 125mm, S3: 150mm, S4/S5: 170mm, S6: 190mm)

ART. NR.	DESCRIZIONE	COLORE	MISURA
93321-5101	SJ COMP	GLOSS WHITE MOUNTAINS1 / BLACK	
93321-5102			S2
93321-5103			S3
93321-5104			S4
93321-5105			S5
93321-5106			S6