

STUMPJUMPER ALLOY



SATIN BLACK / SMOKE

STUMPJUMPER ALLOY	S1	S2	S3	S4	S5	S6
Stack (BB basso) (mm)	618	613	623	631	639	649
Stack (BB alto) (mm)	614	609	618	627	640	644
Reach (BB basso) (mm)	410	430	450	475	500	530
Reach (BB alto) (mm)	416	435	455	480	505	535
Lunghezza Tubo sterzo (mm)	100	100	110	120	130	140
Angolo Sterzo (BB basso) (°)	65	65	65	65	65	65
Angolo Sterzo (BB alto) (°)	65.5	65.5	65.5	65.5	65.5	65.5
Altezza BB (Basso) (mm)	327	332	332	332	332	332
Altezza BB (Alto) (mm)	334	339	339	339	339	339
BB Drop (basso) (mm)	47	42	42	42	42	42
BB Drop (alto) (mm)	40	35	35	35	35	35
Trail (BB basso) (mm)	126	126	126	126	126	126
Trail (BB alto) (mm)	122	122	122	122	122	122
Lunghezza Forcella (intera) (mm)	550	550	550	550	550	550
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	726	746	770	799	828	863
Lunghezza Batticateni (BB basso) (mm)	444	444	444	444	454	454
Lunghezza Batticateni (BB alto) (mm)	440	440	440	440	450	450
Intersasse (BB basso) (mm)	1168	1188	1212	1241	1280	1315
Intersasse (BB alto) (mm)	1164	1184	1208	1237	1276	1311
Top-tube Length (horizontal) (mm)	545	563	586	615	643	676
Bike Standover Height (mm)	742	742	750	753	777	784
Seat Tube Length (mm)	385	385	405	425	445	465
Angolo Sella (BB basso) (°)	77.7	77.7	77.5	77.2	77	76.9
Angolo Sella (BB alto) (°)	78.2	78.2	77.9	77.7	77.5	77.3
Massimo Inserim.Reggisella (mm)	190	190	210	230	250	270
Minimo Inserim.Reggisella (mm)	100	100	100	100	100	100
Lunghezza Pedivella (mm)	165	170	170	170	170	175
Larghezza Manubrio (mm)	780	780	780	780	780	780
Lunghezza attacco manubrio (mm)	40	40	50	50	50	50
Larghezza sella (mm)	155	155	143	143	143	143
Lunghezza reggisella (mm)	356	406	456	496	496	556

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	Alloy chassis and rear-end, asymmetrical design, 29 Trail Geometry, horst pivot BB adjustment, threaded BB, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
AMMORTIZZATORE	X-Fusion O2 Pro RL, Rx Trail Tune, rebound adjust, lockout S1:190x42.5mm, S2-S6: 190x45mm
FORCELLA	RockShox 35 Silver, Solo Air, 44mm offset, rebound adjust, TurnKey lockout, 15x110mm Boost™ Maxle® Lite thru-axle, 140mm of travel
ATTACCO	Alloy Trail Stem, 35mm bar bore
MANUBRIO	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 800mm width
FRENO ANT.	Tektro Gemini Comp, hydraulic disc, resin pad, 200mm
FRENO POST.	Tektro Gemini Comp, hydraulic disc, resin pad, 180mm
CAMBIO POST.	SRAM SX Eagle, 12-speed
COMANDI	SRAM SX Eagle, trigger, 12-speed
CATENA	SRAM SX Eagle, 12-speed
GUARNITURA	SRAM SX Eagle, DUB, S1:165mm, S2-S5: 170mm, S6: 175mm
INGRANAGGI	Steel, 30T
CERCHI	700c disc, double-wall alloy, sleeved, 32h
MOZZO ANT.	Alloy, sealed cartridge bearings, 15x10mm thru-axle, 28h
MOZZO POST.	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Butcher, GRID casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Purgatory, GRID Casing, GRIPTON® compound, 29x2.3"
SELLA	Body Geometry Bridge Saddle, steel rails
REGGISELLA	TranzX dropper, 34.9mm, XS-S: 100mm, M: 120mm, L/XL: 150mm Travel

ART. NR.	DESCRIZIONE	COLORE	MISURA
93321-7002	SJ ALLOY	SATIN BLACK / SMOKE	S2
93321-7003			S3
93321-7004			S4
93321-7005			S5