

S-WORKS STUMPJUMPER EVO



Rosso / Nero / Carbonio

S-WORKS STUMPJUMPER EVO	S2	S3	S4	S5
Stack (mm)	617	626	635	644
Reach (mm)	428	448	475	498
Headtube Length (mm)	95	105	115	125
Headtube Angle (°)	64.5	64.5	64.5	64.5
BB Height (mm)	340	340	340	340
BB Drop (mm)	35	35	35	35
Trail (mm)	131	131	131	131
Lunghezza Forcella (mm)	571	571	571	571
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	756	780	809	838
Chainstay Length (mm)	438	438	438	448
Wheelbase (mm)	1191	1216	1247	1285
Top-tube Length (horizontal) (mm)	564	590	623	647
Bike Standover Height (mm)	764	763	762	767
Seat Tube Length (mm)	385	405	425	445
Seat Tube Angle (°)	77.6	77.2	76.9	77
Max Seatpost Insertion (mm)	180	200	220	240
Min Seatpost Insertion (mm)	80	80	80	80
Lunghezza Pedivella (mm)	170	170	170	170
Larghezza Manubrio (mm)	800	800	800	800
Lunghezza attacco manubrio (mm)	35	50	50	50
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella (mm)	125	150	170	170

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	FACT 11m carbon chassis and rear-end, asymmetrical design, 29 Trail Geometry, SWAT™ Door integration, head tube angle adjustment, horst pivot BB adjustment, threaded BB, fully enclosed internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm of travel
SWAT	Increased-volume SWAT™ Door integration with 22oz SWAT™ Bladder
AMMORTIZZATORE	FOX FLOAT DPX2 Factory, Rx Trail Tune, EVOL Air sleeve, Kashima coat, 3-position adjustment w/ Open Mode adjustment, S1:210x50mm, S2-S6:210x55mm
FORCELLA	FOX FLOAT 36 Factory, GRIP2 damper, Kashima Coating, 15x110mm, 44mm offset, S1: 150mm of travel, S2-S6: 160mm of travel
ATTACCO	Deity Copperhead, 35.0mm
MANUBRIO	Roval Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, 800mm, 35.0mm
MANOPOLE	Deity, Knuckleduster, Black
FRENO ANT.	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
CAMBIO POST.	SRAM XX1 Eagle AXS
COMANDI	SRAM XX1 Eagle AXS
CATENA	SRAM XX1, 12 speed
GUARNITURA	SRAM X01 Eagle, DUB, S1:165mm, S2-S5: 170mm, S6: 175mm
INGRANAGGI	Steel, 30T
CERCHI	Roval Traverse SL 29, hookless carbon, 30mm inner width, 2Bliss Ready, hand-built, 28h
MOZZO ANT.	Roval Traverse SL, sealed cartridge bearings, 15mm thru-axle, 110mm spacing
MOZZO POST.	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing
RAGGI	DT Competition Race
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
SELLA	Bridge, 155/143mm, Hollow Ti-rails
REGGISELLA	RockShox Reverb AXS, 30.9, 1X remote, (S1:100mm, S2: 125mm, S3: 150mm, S4-S6: 170mm)

ART. NR.	DESCRIZIONE	COLORE	MISURA
96321-0102	SJ EVO SW	Rosso / Nero / Carbonio	S2
96321-0103			S3
96321-0104			S4
96321-0105			S5