

STUMPJUMPER EVO COMP



Nero Satinato / Grigio Fumo

STUMPJUMPER EVO COMP	S2	S3	S4	S5
Stack (mm)	617	626	635	644
Reach (mm)	428	448	475	498
Headtube Length (mm)	95	105	115	125
Headtube Angle (°)	64.5	64.5	64.5	64.5
BB Height (mm)	340	340	340	340
BB Drop (mm)	35	35	35	35
Trail (mm)	131	131	131	131
Lunghezza Forcella (mm)	571	571	571	571
Fork Rake/Offset (mm)	44	44	44	44
Front Center (mm)	756	780	809	838
Chainstay Length (mm)	438	438	438	448
Wheelbase (mm)	1191	1216	1247	1285
Top-tube Length (horizontal) (mm)	564	590	623	647
Bike Standover Height (mm)	764	763	762	767
Seat Tube Length (mm)	385	405	425	445
Seat Tube Angle (°)	77.6	77.2	76.9	77
Max Seatpost Insertion (mm)	180	200	220	240
Min Seatpost Insertion (mm)	80	80	80	80
Lunghezza Pedivella ()	170	170	170	170
Larghezza Manubrio (mm)	800	800	800	800
Lunghezza attacco manubrio ()	40	50	50	50
Larghezza sella (mm)	155	143	143	143
Lunghezza reggisella ()	361.5	425.5	470.5	470.5

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	FACT 11m carbon chassis and rear-end, asymmetrical design, 29 Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, fully enclosed internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm of travel
SWAT	Increased-volume SWAT™ Door integration with 22oz SWAT™ Bladder
AMMORTIZZATORE	FOX FLOAT DPX2 Performance, Rx Trail Tune, EVOL Air sleeve, Kashima coat, 3-position adjustment, S1:210x50mm, S2-S6:210x55mm
FORCELLA	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, S1:150mm of travel, S2-S6:160mm of travel
ATTACCO	Alloy Trail Stem, 35mm bar bore
MANUBRIO	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 800mm width
FRENO ANT.	Shimano SLX M7120, 4-piston caliper, hydraulic disc, 200mm
FRENO POST.	Shimano SLX M7120, 4-piston caliper, hydraulic disc, 180mm
CAMBIO POST.	Shimano SLX M7100, SGS, 12-speed
COMANDI	Shimano SLX, M7100, 12spd
CATENA	Shimano SLX, M7100, 12-speed
GUARNITURA	Shimano SLX, S1:165mm, S2-S5: 170mm, S6: 175mm
INGRANAGGI	30T
CERCHI	Roval 29, hookless alloy, 30mm inner width, tubeless ready
MOZZO ANT.	Shimano MT400-B, Centerlock 28h, 15x110 Boost
MOZZO POST.	Shimano MT510-B, Centerlock 28h, 12x148 Boost, Microspline
RAGGI	DT Swiss Industry
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® compound, 29x2.3"
SELLA	Bridge Comp, Hollow Cr-mo rails, 155/143mm
REGGISELLA	X-Fusion Manic, infinite adjustable, remote SRL LE lever, 34.9 (S1:100mm, S2: 125mm, S3: 150mm, S4/S5: 170mm, S6: 190mm)

ART. NR.	DESCRIZIONE	COLORE	MISURA
96321-5102	SJ EVO EXPERT	Nero Satinato / Grigio Fumo	S2
96321-5103			S3
96321-5104			S4
96321-5105			S5