

TURBO LEVO PRO



Satin Redwood / Smoke / Black

TURBO LEVO PRO	S1	S2	S3	S4	S5	S6
Stack (mm)	605	617	626	635	644	653
Roach (mm)	412	432	452	477	502	532
Lunghezza Tubo sterzo (mm)	105	105	115	125	135	145
Angolo Sterzo (°)	64,5	64,5	64,5	64,5	64,5	64,5
Altezza BB (mm)	352	350	350	350	350	350
BB Drop (mm)	25	27	27	27	27	27
Trail (mm)	130	130	130	130	130	130
Lunghezza Forcella (intera) (mm)	557	567	567	567	567	567
Offset forcella / Rake (mm)	44	44	44	44	44	44
Avancorsa (mm)	738	760	784	814	843	878
Lunghezza Batticateni (mm)	442	442	442	442	442	442
Interasse (mm)	1179	1200	1225	1255	1284	1318
Altezza Standover (mm)	752	776	783	787	788	790
Lunghezza piantone (mm)	380	390	405	425	445	465
Angolo Sella (°)	78	77,2	76,7	76,2	76,2	76,2
Max Inserim.Reggisella (mm)	210	220	240	255	275	295
Min Inserim.Reggisella (mm)	80	80	80	80	80	80
Lunghezza Pedivella (mm)	160	160	160	160	160	160
Larghezza Manubrio (mm)	780	780	780	780	780	780
Lunghezza attacco manubrio (mm)	35	50	50	50	50	50
Larghezza sella (mm)	155	143	143	143	143	143
Lunghezza reggisella (mm)	125	150	175	175	200	200

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	FACT 11m full carbon, 29" front wheel, 27,5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot
AMMORTIZZATORE	FOX FLOAT X2 Factory, LSC, LSR, 2-position lever, 55x210mm, Kashima
FORCELLA	FOX FLOAT 38 Factory 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1,5" tapered steerer, 160mm travel, Kashima
ATTACCO	Deity Copperhead, 35,0mm
MANUBRIO	Specialized Trail, FACT Carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 35mm
MANOPOLE	Deity, Knuckleduster, Black
FRENO ANT.	SRAM Code RSC, 4-piston caliper, hydraulic disc, S1-S3: 200mm, S4-S6: 220mm
FRENO POST.	SRAM Code RSC, 4-piston caliper, hydraulic disc, 200mm
CAMBIO POST.	Sram X01 Eagle, 12-speed
COMANDI	SRAM X01 Eagle trigger, 12-speed, single click
CASSETTA	SRAM XG-1295 Eagle, 10-52t
CATENA	SRAX X01 Eagle, 12-speed
GUARNITURA	Praxis Carbon M30, custom offset, 160mm
INGRANAGGI	SRAM X-Sync Eagle, 104 BCD, 32T, steel
RUOTA ANT.	Traverse Carbon 29
RUOTA POST.	Traverse Carbon 27,5
PNEUMATICO ANT.	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2,6"
PNEUMATICO POST.	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27,5x2,6"
SELLA	Bridge, 155/143mm, Hollow Ti-rails
REGGISELLA	FOX Transfer, 30,9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 200mm
MOTORE	Specialized Turbo Full Power System 2.2 Motor
UI/REMOTE	Specialized MasterMind TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote
BATTERIA	Specialized M3-700, Integrated battery, 700Wh
CARICATORE	Custom charger, 42V4A w/ Rosenberger plug
CABLAGGIO	Custom Specialized wiring harness
SWAT	SWAT CC steerer tube integrated tool with chain tool and link

ART. NR.	DESCRIZIONE	COLORE	MISURA
95221-1102	LEVO PRO CARBON NB	Satin Redwood / Smoke / Black	S2
95221-1103			S3
95221-1104			S4
95221-1105			S5
95221-1106			S6